

Package: tidyHeatmap (via r-universe)

March 11, 2025

Type Package

Title A Tidy Implementation of Heatmap

Version 1.11.6

Maintainer Stefano Mangiola <mangiolastefano@gmail.com>

Description This is a tidy implementation for heatmap. At the moment it is based on the (great) package 'ComplexHeatmap'. The goal of this package is to interface a tidy data frame with this powerful tool. Some of the advantages are: Row and/or columns colour annotations are easy to integrate just specifying one parameter (column names). Custom grouping of rows is easy to specify providing a grouped tbl. For example: `df %>% group_by(...)`. Labels size adjusted by row and column total number. Default use of Brewer and Viridis palettes.

License GPL-3

URL <https://www.r-project.org>,
<https://github.com/stemangiola/tidyHeatmap>

BugReports <https://github.com/stemangiola/tidyHeatmap/issues>

Depends R (>= 4.3.0)

Imports methods, stats, utils, dplyr (>= 0.8.5), magrittr (>= 1.5), tidyr (>= 1.0.3), rlang (>= 0.4.5), purrr (>= 0.3.3), tibble, ComplexHeatmap (>= 2.2.0), viridis (>= 0.5.1), circlize (>= 0.4.8), RColorBrewer (>= 1.1), grid, grDevices, lifecycle (>= 0.2.0), dendextend, patchwork

Suggests spelling, testthat, vdiff, BiocManager, knitr, rmarkdown, qpdf, covr, roxygen2, forcats, ggplot2

VignetteBuilder knitr

RdMacros lifecycle

Biarch true

biocViews AssayDomain, Infrastructure

Encoding UTF-8

LazyData true
RoxygenNote 7.3.2
Language en-US
NeedsCompilation no
Author Stefano Mangiola [aut, cre], Anthony Papenfuss [ctb]
Repository CRAN
Date/Publication 2025-02-08 04:20:02 UTC
Config/pak/sysreqs libicu-dev libpng-dev perl

Contents

add_annotation	3
add_attr	4
add_bar	5
add_class	6
add_line	7
add_point	8
add_tile	9
annotation_bar	10
annotation_line	11
annotation_numeric	12
annotation_point	14
annotation_tile	15
annot_to_list	17
as_ComplexHeatmap	17
as_matrix	18
check_if_counts_is_na	19
check_if_duplicated_genes	19
check_if_wrong_input	20
drop_class	20
error_if_log_transformed	21
get_abundance_norm_if_exists	21
get_elements	22
get_elements_features	22
get_elements_features_abundance	23
get_sample_counts	23
get_sample_transcript	24
get_sample_transcript_counts	24
get_x_y_annotation_columns	25
heatmap	25
ifelse2_pipe	28
ifelse_pipe	28
input_heatmap	29
layer_arrow_down	30
layer_arrow_up	31

layer_asterisk 33
 layer_diamond 34
 layer_point 35
 layer_square 36
 layer_star 38
 layer_text 39
 N52 40
 parse_formula 41
 pasilla 41
 prepend 42
 quo_names 42
 save_pdf 43
 save_pdf,Heatmap-method 44
 save_pdf,InputHeatmap-method 45
 scale_robust 45
 select_closest_pairs 46
 split_rows 46
 wrap_heatmap 48

Index **50**

add_annotation *add_annotation*

Description

add_annotation() takes a tbl object and easily produces a ComplexHeatmap plot, with integration with tibble and dplyr frameworks.

Usage

```
add_annotation(  
  my_input_heatmap,  
  annotation,  
  type = rep("tile", length(quo_names(annotation))),  
  palette_discrete = list(),  
  palette_continuous = list(),  
  size = NULL,  
  ...  
)
```

Arguments

my_input_heatmap A 'InputHeatmap' formatted as |<SAMPLE> |<TRANSCRIPT> |<COUNT> |<...> |
 annotation Vector of quotes
 type A character vector of the set c("\tile", "\point", "\bar", "\line")

palette_discrete	A list of character vectors. This is the list of palettes that will be used for horizontal and vertical discrete annotations. The discrete classification of annotations depends on the column type of your input tibble (e.g., character and factor).
palette_continuous	A list of character vectors. This is the list of palettes that will be used for horizontal and vertical continuous annotations. The continuous classification of annotations depends on the column type of your input tibble (e.g., integer, numerical, double).
size	A grid::unit object, e.g. unit(2, "cm"). This is the height or width of the annotation depending on the orientation.
...	The arguments that will be passed to top_annotation or left_annotation of the ComplexHeatmap container

Details

To be added.

Value

A 'ComplexHeatmap' object

Source

[Mangiola and Papenfuss., 2020](<https://joss.theoj.org/papers/10.21105/joss.02472>)

References

Mangiola, S. and Papenfuss, A.T., 2020. "tidyHeatmap: an R package for modular heatmap production based on tidy principles." Journal of Open Source Software. doi:10.21105/joss.02472.

add_attr	<i>Add attribute to object</i>
----------	--------------------------------

Description

Add attribute to object

Usage

```
add_attr(var, attribute, name)
```

Arguments

var	A tibble
attribute	An object
name	A character name of the attribute

Value

A tibble with an additional attribute

add_bar	<i>DEPRECATED. Adds a bar annotation layer to a 'InputHeatmap', that on evaluation creates a 'ComplexHeatmap'</i>
---------	---

Description

add_bar() from a 'InputHeatmap' object, adds a bar annotation layer.

add_bar() from a 'InputHeatmap' object, adds a bar annotation layer.

Usage

```
add_bar(.data, .column, palette = NULL, size = NULL, ...)
```

```
add_bar(.data, .column, palette = NULL, size = NULL, ...)
```

```
## S4 method for signature 'InputHeatmap'
```

```
add_bar(.data, .column, palette = NULL, size = NULL, ...)
```

Arguments

.data	A 'tbl_df' formatted as <ELEMENT> <FEATURE> <VALUE> <...>
.column	Vector of quotes
palette	A character vector of colors, or a function such as colorRamp2 (see examples).
size	A grid::unit object, e.g. unit(2, "cm"). This is the height or width of the annotation depending on the orientation.
...	The arguments that will be passed to top_annotation or left_annotation of the ComplexHeatmap container

Details**[Maturing]**

It uses 'ComplexHeatmap' as visualisation tool.

[Maturing]

It uses 'ComplexHeatmap' as visualisation tool.

Value

A 'InputHeatmap' object that gets evaluated to a 'ComplexHeatmap'

A 'InputHeatmap' object that gets evaluated to a 'ComplexHeatmap'

A 'InputHeatmap' object that gets evaluated to a 'ComplexHeatmap'

Source

[Mangiola and Papenfuss., 2020](<https://joss.theoj.org/papers/10.21105/joss.02472>)

References

Mangiola, S. and Papenfuss, A.T., 2020. "tidyHeatmap: an R package for modular heatmap production based on tidy principles." *Journal of Open Source Software*. doi:10.21105/joss.02472.

Examples

```
print("DEPRECATED")
```

```
print("DEPRECATED")
```

add_class	<i>Add class to object</i>
-----------	----------------------------

Description

Add class to object

Usage

```
add_class(var, name)
```

Arguments

var	A tibble
name	A character name of the attribute

Value

A tibble with an additional attribute

add_line	<i>DEPRECATED. Adds a line annotation layer to a 'InputHeatmap', that on evaluation creates a 'ComplexHeatmap'</i>
----------	--

Description

add_line() from a 'InputHeatmap' object, adds a line annotation layer.

Usage

```
add_line(.data, .column, palette = NULL, size = NULL, ...)
```

```
## S4 method for signature 'InputHeatmap'
add_line(.data, .column, palette = NULL, size = NULL, ...)
```

Arguments

.data	A 'tbl_df' formatted as <ELEMENT> <FEATURE> <VALUE> <...>
.column	Vector of quotes
palette	A character vector of colors, or a function such as colorRamp2 (see examples).
size	A grid::unit object, e.g. unit(2, "cm"). This is the height or width of the annotation depending on the orientation.
...	The arguments that will be passed to top_annotation or left_annotation of the ComplexHeatmap container

Details

[Maturing]

It uses 'ComplexHeatmap' as visualisation tool.

Value

A 'InputHeatmap' object that gets evaluated to a 'ComplexHeatmap'

A 'InputHeatmap' object that gets evaluated to a 'ComplexHeatmap'

Source

[Mangiola and Papenfuss., 2020](<https://joss.theoj.org/papers/10.21105/joss.02472>)

References

Mangiola, S. and Papenfuss, A.T., 2020. "tidyHeatmap: an R package for modular heatmap production based on tidy principles." Journal of Open Source Software. doi:10.21105/joss.02472.

Examples

```
print("DEPRECATED")
```

add_point	<i>DEPRECATED. Adds a point annotation layer to a 'InputHeatmap', that on evaluation creates a 'ComplexHeatmap'</i>
-----------	---

Description

add_point() from a 'InputHeatmap' object, adds a point annotation layer.

Usage

```
add_point(.data, .column, palette = NULL, size = NULL, ...)
```

```
## S4 method for signature 'InputHeatmap'
add_point(.data, .column, palette = NULL, size = NULL, ...)
```

Arguments

.data	A 'tbl_df' formatted as <ELEMENT> <FEATURE> <VALUE> <...>
.column	Vector of quotes
palette	A character vector of colors, or a function such as colorRamp2 (see examples).
size	A grid::unit object, e.g. unit(2, "cm"). This is the height or width of the annotation depending on the orientation.
...	The arguments that will be passed to top_annotation or left_annotation of the ComplexHeatmap container

Details**[Maturing]**

It uses 'ComplexHeatmap' as visualisation tool.

Value

A 'InputHeatmap' object that gets evaluated to a 'ComplexHeatmap'

A 'InputHeatmap' object that gets evaluated to a 'ComplexHeatmap'

Source

[Mangiola and Papenfuss., 2020](<https://joss.theoj.org/papers/10.21105/joss.02472>)

References

Mangiola, S. and Papenfuss, A.T., 2020. "tidyHeatmap: an R package for modular heatmap production based on tidy principles." Journal of Open Source Software. doi:10.21105/joss.02472.

Examples

```
print("DEPRECATED")
```

add_tile	<i>DEPRECATED. Adds a tile annotation layer to a 'InputHeatmap', that on evaluation creates a 'ComplexHeatmap'</i>
----------	--

Description

add_tile() from a 'InputHeatmap' object, adds a tile annotation layer.

Usage

```
add_tile(.data, .column, palette = NULL, size = NULL, ...)
```

```
## S4 method for signature 'InputHeatmap'
```

```
add_tile(.data, .column, palette = NULL, size = NULL, ...)
```

Arguments

.data	A 'tbl_df' formatted as <ELEMENT> <FEATURE> <VALUE> <...>
.column	Vector of quotes
palette	A character vector of colors, or a function such as colorRamp2 (see examples).
size	A grid::unit object, e.g. unit(2, "cm"). This is the height or width of the annotation depending on the orientation.
...	The arguments that will be passed to top_annotation or left_annotation of the ComplexHeatmap container

Details

[Maturing]

It uses 'ComplexHeatmap' as visualisation tool.

Value

A 'InputHeatmap' object that gets evaluated to a 'ComplexHeatmap'

A 'InputHeatmap' object that gets evaluated to a 'ComplexHeatmap'

Source

[Mangiola and Papenfuss., 2020](https://joss.theoj.org/papers/10.21105/joss.02472)

References

Mangiola, S. and Papenfuss, A.T., 2020. "tidyHeatmap: an R package for modular heatmap production based on tidy principles." Journal of Open Source Software. doi:10.21105/joss.02472.

Examples

```
print("DEPRECATED")
```

annotation_bar	<i>Adds a bar annotation layer to a 'InputHeatmap', that on evaluation creates a 'ComplexHeatmap'</i>
----------------	---

Description

annotation_bar() from a 'InputHeatmap' object, adds a bar annotation layer.

Usage

```
annotation_bar(.data, .column, palette = NULL, size = NULL, ...)
```

```
## S4 method for signature 'InputHeatmap'
```

```
annotation_bar(.data, .column, palette = NULL, size = NULL, ...)
```

Arguments

.data	a 'InputHeatmap' object created calling 'tidyHeatmap::heatmap()'
.column	Vector of quotes
palette	A character vector of colors, or a function such as colorRamp2 (see examples).
size	A grid::unit object, e.g. unit(2, "cm"). This is the height or width of the annotation depending on the orientation.
...	The arguments that will be passed to anno_barplot and HeatmapAnnotation if you want to fine tune the aesthetics.

Details**[Maturing]**

It uses 'ComplexHeatmap' as visualisation tool.

Value

A 'InputHeatmap' object that gets evaluated to a 'ComplexHeatmap'

A 'InputHeatmap' object that gets evaluated to a 'ComplexHeatmap'

Source

[Mangiola and Papenfuss., 2020](https://joss.theoj.org/papers/10.21105/joss.02472)

References

Mangiola, S. and Papenfuss, A.T., 2020. "tidyHeatmap: an R package for modular heatmap production based on tidy principles." Journal of Open Source Software. doi:10.21105/joss.02472.

Examples

```
hm =
  tidyHeatmap::N52 |>
  tidyHeatmap::heatmap(
    .row = symbol_ct,
    .column = UBR,
    .value = `read count normalised log`
  )

hm |> annotation_bar(inflexion)
```

annotation_line	<i>Adds a line annotation layer to a 'InputHeatmap', that on evaluation creates a 'ComplexHeatmap'</i>
-----------------	--

Description

annotation_line() from a 'InputHeatmap' object, adds a line annotation layer.

Usage

```
annotation_line(.data, .column, palette = NULL, size = NULL, ...)

## S4 method for signature 'InputHeatmap'
annotation_line(.data, .column, palette = NULL, size = NULL, ...)
```

Arguments

.data	a 'InputHeatmap' object created calling 'tidyHeatmap::heatmap()'
.column	Vector of quotes
palette	A character vector of colors, or a function such as colorRamp2 (see examples).
size	A grid::unit object, e.g. unit(2, "cm"). This is the height or width of the annotation depending on the orientation.
...	The arguments that will be passed to anno_lines and HeatmapAnnotation if you want to fine tune the aesthetics.

Details

[Maturing]

It uses ‘ComplexHeatmap’ as visualisation tool.

Value

A ‘InputHeatmap’ object that gets evaluated to a ‘ComplexHeatmap’

A ‘InputHeatmap’ object that gets evaluated to a ‘ComplexHeatmap’

Source

[Mangiola and Papenfuss., 2020](<https://joss.theoj.org/papers/10.21105/joss.02472>)

References

Mangiola, S. and Papenfuss, A.T., 2020. "tidyHeatmap: an R package for modular heatmap production based on tidy principles." Journal of Open Source Software. doi:10.21105/joss.02472.

Examples

```
hm =  
  tidyHeatmap::N52 |>  
  tidyHeatmap::heatmap(  
    .row = symbol_ct,  
    .column = UBR,  
    .value = `read count normalised log`  
  )  
  
hm |> annotation_line(inflexion)
```

annotation_numeric	<i>Adds a numeric annotation layer to an ‘InputHeatmap’, that on evaluation creates a ‘ComplexHeatmap’</i>
--------------------	--

Description

‘annotation_numeric()’ from an ‘InputHeatmap’ object adds a numeric annotation layer.

Usage

```

annotation_numeric(
  .data,
  .column,
  palette = NULL,
  size = NULL,
  labels_format = function(x) sprintf("%.1f", x),
  ...
)

## S4 method for signature 'InputHeatmap'
annotation_numeric(
  .data,
  .column,
  palette = NULL,
  size = NULL,
  labels_format = function(x) sprintf("%.1f", x),
  ...
)

```

Arguments

.data	A ‘tbl_df’ formatted as <ELEMENT> <FEATURE> <VALUE> <...>
.column	Vector of quotes
palette	A character vector of colours, or a function such as <code>colorRamp2</code> (see examples).
size	A <code>grid::unit</code> object, e.g. <code>unit(2, "cm")</code> . This is the height or width of the annotation depending on the orientation.
labels_format	A function to format the numeric labels. By default, it formats numbers to two decimal places using ‘ <code>sprintf("</code> supply any function that takes a numeric vector and returns a character vector for customised formatting.
...	The arguments that will be passed to <code>anno_numeric</code> and <code>HeatmapAnnotation</code> if you want to fine tune the aesthetics.

Details**[Maturing]**

It uses ‘ComplexHeatmap’ as the visualisation tool.

Value

An ‘InputHeatmap’ object that gets evaluated to a ‘ComplexHeatmap’.

An ‘InputHeatmap’ object that gets evaluated to a ‘ComplexHeatmap’.

Source

[Mangiola and Papenfuss, 2020](<https://joss.theoj.org/papers/10.21105/joss.02472>)

References

Mangiola, S. and Papenfuss, A.T., 2020. "tidyHeatmap: an R package for modular heatmap production based on tidy principles." Journal of Open Source Software. doi:10.21105/joss.02472.

Examples

```
hm =
  tidyHeatmap::N52 |>
  tidyHeatmap::heatmap(
    .row = symbol_ct,
    .column = UBR,
    .value = `read count normalised log`
  )

hm |> annotation_numeric(inflexion)

# Align to the right
hm |> annotation_numeric(inflexion, align_to = "right")
```

annotation_point	<i>Adds a point annotation layer to a 'InputHeatmap', that on evaluation creates a 'ComplexHeatmap'</i>
------------------	---

Description

annotation_point() from a 'InputHeatmap' object, adds a point annotation layer.

Usage

```
annotation_point(.data, .column, palette = NULL, size = NULL, ...)

## S4 method for signature 'InputHeatmap'
annotation_point(.data, .column, palette = NULL, size = NULL, ...)
```

Arguments

.data	a 'InputHeatmap' object created calling 'tidyHeatmap::heatmap()'
.column	Vector of quotes
palette	A character vector of colors, or a function such as colorRamp2 (see examples).
size	A grid::unit object, e.g. unit(2, "cm"). This is the height or width of the annotation depending on the orientation.
...	The arguments that will be passed to anno_points and HeatmapAnnotation if you want to fine tune the aesthetics.

Details**[Maturing]**

It uses ‘ComplexHeatmap’ as visualisation tool.

Value

A ‘InputHeatmap’ object that gets evaluated to a ‘ComplexHeatmap’

A ‘InputHeatmap’ object that gets evaluated to a ‘ComplexHeatmap’

Source

[Mangiola and Papenfuss., 2020](<https://joss.theoj.org/papers/10.21105/joss.02472>)

References

Mangiola, S. and Papenfuss, A.T., 2020. "tidyHeatmap: an R package for modular heatmap production based on tidy principles." Journal of Open Source Software. doi:10.21105/joss.02472.

Examples

```
hm =
  tidyHeatmap::N52 |>
  tidyHeatmap::heatmap(
    .row = symbol_ct,
    .column = UBR,
    .value = `read count normalised log`
  )

hm |> annotation_point(inflexion)
```

annotation_tile	<i>Adds a tile annotation layer to a ‘InputHeatmap’, that on evaluation creates a ‘ComplexHeatmap’</i>
-----------------	--

Description

annotation_tile() from a ‘InputHeatmap’ object, adds a tile annotation layer.

Usage

```
annotation_tile(.data, .column, palette = NULL, size = NULL, ...)

## S4 method for signature 'InputHeatmap'
annotation_tile(.data, .column, palette = NULL, size = NULL, ...)
```

Arguments

<code>.data</code>	a ‘InputHeatmap’ object created calling ‘tidyHeatmap::heatmap()’
<code>.column</code>	Vector of quotes
<code>palette</code>	A character vector of colors, or a function such as <code>colorRamp2</code> (see examples).
<code>size</code>	A <code>grid::unit</code> object, e.g. <code>unit(2, "cm")</code> . This is the height or width of the annotation depending on the orientation.
<code>...</code>	The arguments that will be passed to <code>anno_block</code> and <code>HeatmapAnnotation</code> if you want to fine tune the aesthetics.

Details**[Maturing]**

It uses ‘ComplexHeatmap’ as visualisation tool.

Value

A ‘InputHeatmap’ object that gets evaluated to a ‘ComplexHeatmap’

A ‘InputHeatmap’ object that gets evaluated to a ‘ComplexHeatmap’

Source

[Mangiola and Papenfuss., 2020](<https://joss.theoj.org/papers/10.21105/joss.02472>)

References

Mangiola, S. and Papenfuss, A.T., 2020. "tidyHeatmap: an R package for modular heatmap production based on tidy principles." *Journal of Open Source Software*. doi:10.21105/joss.02472.

Examples

```

hm =
  tidyHeatmap::N52 |>
  tidyHeatmap::heatmap(
    .row = symbol_ct,
    .column = UBR,
    .value = `read count normalised log`
  )

hm |> annotation_tile(CAPRA_TOTAL)

hm |>
  annotation_tile(
    inflection,
    palette = circlize::colorRamp2(c(0, 3,10), c("white", "green", "red"))
  )

```

annot_to_list	<i>annot_to_list</i>
---------------	----------------------

Description

annot_to_list

Usage

```
annot_to_list(.data)
```

Arguments

.data A data frame

Value

A list

as_ComplexHeatmap	<i>Creates a 'ComplexHeatmap' object for less standard plot manipulation (e.g. changing legend position)</i>
-------------------	--

Description

as_ComplexHeatmap() takes a 'InputHeatmap' object and produces a 'Heatmap' object

Usage

```
as_ComplexHeatmap(tidyHeatmap)
```

```
## S4 method for signature 'InputHeatmap'
as_ComplexHeatmap(tidyHeatmap)
```

Arguments

tidyHeatmap A 'InputHeatmap' object from tidyHeatmap::heatmap() call

Details

[Maturing]

Value

A 'ComplexHeatmap'

Source

[Mangiola and Papenfuss., 2020](https://joss.theoj.org/papers/10.21105/joss.02472)

[Mangiola and Papenfuss., 2020](https://joss.theoj.org/papers/10.21105/joss.02472)

References

Mangiola, S. and Papenfuss, A.T., 2020. "tidyHeatmap: an R package for modular heatmap production based on tidy principles." Journal of Open Source Software. doi:10.21105/joss.02472.

Mangiola, S. and Papenfuss, A.T., 2020. "tidyHeatmap: an R package for modular heatmap production based on tidy principles." Journal of Open Source Software. doi:10.21105/joss.02472.

Examples

```
tidyHeatmap::N52 |>
tidyHeatmap::heatmap(
  .row = symbol_ct,
  .column = UBR,
  .value = `read count normalised log`,
) |>
as_ComplexHeatmap()
```

as_matrix

Get matrix from tibble

Description

Get matrix from tibble

Usage

```
as_matrix(tbl, rownames = NULL, do_check = TRUE)
```

Arguments

tbl	A tibble
rownames	A character string of the rownames
do_check	A boolean

Value

A matrix

check_if_counts_is_na *Check whether there are NA counts*

Description

Check whether there are NA counts

Usage

```
check_if_counts_is_na(.data, .abundance)
```

Arguments

.data A tibble of read counts
.abundance A character name of the read count column

Value

A tbl

check_if_duplicated_genes
Check whether there are duplicated genes/transcripts

Description

Check whether there are duplicated genes/transcripts

Usage

```
check_if_duplicated_genes(.data, .sample, .transcript, .abundance)
```

Arguments

.data A tibble of read counts
.sample A character name of the sample column
.transcript A character name of the transcript/gene column
.abundance A character name of the read count column

Value

A tbl

check_if_wrong_input *Check whether there are NA counts*

Description

Check whether there are NA counts

Usage

```
check_if_wrong_input(.data, list_input, expected_type)
```

Arguments

.data A tibble of read counts
list_input A list
expected_type A character string

Value

A tbl

drop_class *Remove class to object*

Description

Remove class to object

Usage

```
drop_class(var, name)
```

Arguments

var A tibble
name A character name of the class

Value

A tibble with an additional attribute

`error_if_log_transformed`*Check whether a numeric vector has been log transformed*

Description

Check whether a numeric vector has been log transformed

Usage

```
error_if_log_transformed(x, .abundance)
```

Arguments

<code>x</code>	A numeric vector
<code>.abundance</code>	A character name of the transcript/gene abundance column

Value

NA

`get_abundance_norm_if_exists`*Get column names either from user or from attributes*

Description

Get column names either from user or from attributes

Usage

```
get_abundance_norm_if_exists(.data, .abundance)
```

Arguments

<code>.data</code>	A tibble
<code>.abundance</code>	A character name of the abundance column

Value

A list of column enquo or error

get_elements	<i>Get column names either from user or from attributes</i>
--------------	---

Description

Get column names either from user or from attributes

Usage

```
get_elements(.data, .element, of_samples = TRUE)
```

Arguments

.data	A tibble
.element	A character name of the sample column
of_samples	A boolean

Value

A list of column enquo or error

get_elements_features	<i>Get column names either from user or from attributes</i>
-----------------------	---

Description

Get column names either from user or from attributes

Usage

```
get_elements_features(.data, .element, .feature, of_samples = TRUE)
```

Arguments

.data	A tibble
.element	A character name of the sample column
.feature	A character name of the transcript/gene column
of_samples	A boolean

Value

A list of column enquo or error

`get_elements_features_abundance`*Get column names either from user or from attributes*

Description

Get column names either from user or from attributes

Usage

```
get_elements_features_abundance(  
  .data,  
  .element,  
  .feature,  
  .abundance,  
  of_samples = TRUE  
)
```

Arguments

<code>.data</code>	A tibble
<code>.element</code>	A character name of the sample column
<code>.feature</code>	A character name of the transcript/gene column
<code>.abundance</code>	A character name of the read count column
<code>of_samples</code>	A boolean

Value

A list of column enquo or error

`get_sample_counts`*Get column names either from user or from attributes*

Description

Get column names either from user or from attributes

Usage

```
get_sample_counts(.data, .sample, .abundance)
```

Arguments

<code>.data</code>	A tibble
<code>.sample</code>	A character name of the sample column
<code>.abundance</code>	A character name of the read count column

Value

A list of column enquo or error

get_sample_transcript *Get column names either from user or from attributes*

Description

Get column names either from user or from attributes

Usage

```
get_sample_transcript(.data, .sample, .transcript)
```

Arguments

.data	A tibble
.sample	A character name of the sample column
.transcript	A character name of the transcript/gene column

Value

A list of column enquo or error

get_sample_transcript_counts
Get column names either from user or from attributes

Description

Get column names either from user or from attributes

Usage

```
get_sample_transcript_counts(.data, .sample, .transcript, .abundance)
```

Arguments

.data	A tibble
.sample	A character name of the sample column
.transcript	A character name of the transcript/gene column
.abundance	A character name of the read count column

Value

A list of column enquo or error

```
get_x_y_annotation_columns
      get_x_y_annotation_columns
```

Description

get_x_y_annotation_columns

Usage

```
get_x_y_annotation_columns(.data, .column, .row, .abundance)
```

Arguments

.data	A 'tbl' formatted as <SAMPLE> <TRANSCRIPT> <COUNT> <...>
.column	The name of the column horizontally presented in the heatmap
.row	The name of the column vertically presented in the heatmap
.abundance	The name of the transcript/gene abundance column

Value

A list

heatmap	<i>Creates a 'InputHeatmap' object from 'tbl_df' on evaluation creates a 'ComplexHeatmap'</i>
---------	---

Description

heatmap() takes a tbl object and easily produces a ComplexHeatmap plot, with integration with tibble and dplyr frameworks.

Usage

```
heatmap(
  .data,
  .row,
  .column,
  .value,
  transform = NULL,
  scale = "none",
  palette_value = c("#440154FF", "#21908CFF", "#fefada"),
  palette_grouping = list(),
  .scale = NULL,
  ...
)
```

```

)

heatmap_(
  .data,
  .row,
  .column,
  .value,
  transform = NULL,
  scale = "none",
  palette_value = c("#440154FF", "#21908CFF", "#fefada"),
  palette_grouping = list(),
  .scale = NULL,
  ...
)

## S4 method for signature 'tbl'
heatmap(
  .data,
  .row,
  .column,
  .value,
  transform = NULL,
  scale = "none",
  palette_value = c("#440154FF", "#21908CFF", "#fefada"),
  palette_grouping = list(),
  .scale = NULL,
  ...
)

## S4 method for signature 'tbl_df'
heatmap(
  .data,
  .row,
  .column,
  .value,
  transform = NULL,
  scale = "none",
  palette_value = c("#440154FF", "#21908CFF", "#fefada"),
  palette_grouping = list(),
  .scale = NULL,
  ...
)

```

Arguments

<code>.data</code>	A 'tbl_df' formatted as <.row> <.column> <.value> <...>
<code>.row</code>	The name of the column vertically presented in the heatmap
<code>.column</code>	The name of the column horizontally presented in the heatmap

<code>.value</code>	The name of the column for the value of the element/feature pair
<code>transform</code>	A function, used to transform <code>.value</code> row-wise (e.g., <code>transform = log1p</code>)
<code>scale</code>	A character string. Possible values are <code>c("none", "row", "column", "both")</code>
<code>palette_value</code>	A character vector This is the palette that will be used as gradient for <code>.value</code> . For example <code>c("red", "white", "blue")</code> . For higher flexibility you can use <code>circlize::colorRamp2(c(-2, -1, 0, 1, 2))</code> , <code>viridis::magma(5)</code>
<code>palette_grouping</code>	A list of character vectors. This is the list of palettes that will be used for grouping. For example <code>list(RColorBrewer::brewer.pal(8, "Accent"))</code> or <code>list(c("#B3E2CD", "#FDCDAC", "#CBD5E8"))</code> or <code>list(c("black", "red"))</code>
<code>.scale</code>	DEPRECATED. please use <code>scale</code> instead (with no dot prefix)
<code>...</code>	The arguments that will be passed to the <code>Heatmap</code> function of <code>ComplexHeatmap</code> backend

Details

[Maturing]

This function takes a `tbl` as an input and creates a ‘ComplexHeatmap’ plot. The information is stored in a ‘InputHeatmap’ object that is updated along the pipe statement, for example adding annotation layers.

Value

A ‘InputHeatmap’ objects that gets evaluated to a ‘ComplexHeatmap’ object

A ‘InputHeatmap’ object

A ‘InputHeatmap’ object

A ‘InputHeatmap’ object

Source

[Mangiola and Papenfuss., 2020](<https://joss.theoj.org/papers/10.21105/joss.02472>)

References

Mangiola, S. and Papenfuss, A.T., 2020. "tidyHeatmap: an R package for modular heatmap production based on tidy principles." *Journal of Open Source Software*. doi:10.21105/joss.02472.

Examples

```
tidyHeatmap::N52 |>
  dplyr::group_by( `Cell type` ) |>
  tidyHeatmap::heatmap(
    .row = symbol_ct,
    .column = UBR,
    .value = `read count normalised log`,
  )
```

ifelse2_pipe	<i>This is a generalisation of ifelse that accepts an object and return an objects</i>
--------------	--

Description

This is a generalisation of ifelse that accepts an object and return an objects

Usage

```
ifelse2_pipe(.x, .p1, .p2, .f1, .f2, .f3 = NULL)
```

Arguments

.x	A tibble
.p1	A boolean
.p2	ELSE IF condition
.f1	A function
.f2	A function
.f3	A function

Value

A tibble

ifelse_pipe	<i>This is a generalisation of ifelse that accepts an object and return an objects</i>
-------------	--

Description

This is a generalisation of ifelse that accepts an object and return an objects

Usage

```
ifelse_pipe(.x, .p, .f1, .f2 = NULL)
```

Arguments

.x	A tibble
.p	A boolean
.f1	A function
.f2	A function

Value

A tibble

input_heatmap	<i>input_heatmap</i>
---------------	----------------------

Description

input_heatmap() takes a tbl object and easily produces a ComplexHeatmap plot, with integration with tibble and dplyr frameworks.

Usage

```
input_heatmap(
  .data,
  .horizontal,
  .vertical,
  .abundance,
  transform = NULL,
  scale = "none",
  palette_value = c("#440154FF", "#21908CFF", "#fefada"),
  palette_grouping = list(),
  ...
)
```

Arguments

.data	A 'tbl' formatted as <SAMPLE> <TRANSCRIPT> <COUNT> <...>
.horizontal	The name of the column horizontally presented in the heatmap
.vertical	The name of the column vertically presented in the heatmap
.abundance	The name of the transcript/gene abundance column
transform	A function, used to transform .value, for example log1p
scale	A character string. Possible values are c("\none\", \"row\", \"column\", \"both\")
palette_value	A character vector, or a function for higher customisation (colorRamp2). This is the palette that will be used as gradient for abundance. If palette_value is a vector of hexadecimal colours, it should have 3 values. If you want more customisation, you can pass to palette_value a function, that is derived as for example 'colorRamp2(c(-2, 0, 2), palette_value)'
palette_grouping	A list of character vectors. This is the list of palettes that will be used for grouping
...	Further arguments to be passed to ComplexHeatmap::Heatmap

Details

To be added.

Value

A ‘ComplexHeatmap’ object

Source

[Mangiola and Papenfuss., 2020](https://joss.theoj.org/papers/10.21105/joss.02472)

References

Mangiola, S. and Papenfuss, A.T., 2020. "tidyHeatmap: an R package for modular heatmap production based on tidy principles." Journal of Open Source Software. doi:10.21105/joss.02472.

layer_arrow_down	<i>Adds a layers of symbols above the heatmap tiles to a ‘InputHeatmap’, that on evaluation creates a ‘ComplexHeatmap’</i>
------------------	--

Description

layer_arrow_down() from a ‘InputHeatmap’ object, adds a bar annotation layer.

Usage

```
layer_arrow_down(.data, ..., .size = NULL)
```

```
## S4 method for signature 'InputHeatmap'
layer_arrow_down(.data, ..., .size = NULL)
```

Arguments

.data	A ‘InputHeatmap’
...	Expressions that return a logical value, and are defined in terms of the variables in .data. If multiple expressions are included, they are combined with the & operator. Only rows for which all conditions evaluate to TRUE are kept.
.size	A column name or a double. The size of the elements of the layer.

Details**[Maturing]**

It uses ‘ComplexHeatmap’ as visualisation tool.

Value

A ‘InputHeatmap’ object that gets evaluated to a ‘ComplexHeatmap’

A ‘InputHeatmap’ object that gets evaluated to a ‘ComplexHeatmap’

Source

[Mangiola and Papenfuss., 2020](https://joss.theoj.org/papers/10.21105/joss.02472)

References

Mangiola, S. and Papenfuss, A.T., 2020. "tidyHeatmap: an R package for modular heatmap production based on tidy principles." Journal of Open Source Software. doi:10.21105/joss.02472.

Examples

```
hm =
  tidyHeatmap::N52 |>
  tidyHeatmap::heatmap(
    .row = symbol_ct,
    .column = UBR,
    .value = `read count normalised log`
  )

hm |> layer_arrow_down()
```

layer_arrow_up	<i>Adds a layers of symbols above the heatmap tiles to a ‘InputHeatmap’, that on evaluation creates a ‘ComplexHeatmap’</i>
----------------	--

Description

layer_arrow_up() from a ‘InputHeatmap’ object, adds a bar annotation layer.

Usage

```
layer_arrow_up(.data, ..., .size = NULL)

## S4 method for signature 'InputHeatmap'
layer_arrow_up(.data, ..., .size = NULL)
```

Arguments

<code>.data</code>	A 'InputHeatmap'
<code>...</code>	Expressions that return a logical value, and are defined in terms of the variables in <code>.data</code> . If multiple expressions are included, they are combined with the <code>&</code> operator. Only rows for which all conditions evaluate to TRUE are kept.
<code>.size</code>	A column name or a double. The size of the elements of the layer.

Details**[Maturing]**

It uses 'ComplexHeatmap' as visualisation tool.

Value

A 'InputHeatmap' object that gets evaluated to a 'ComplexHeatmap'

A 'InputHeatmap' object that gets evaluated to a 'ComplexHeatmap'

Source

[Mangiola and Papenfuss., 2020](<https://joss.theoj.org/papers/10.21105/joss.02472>)

References

Mangiola, S. and Papenfuss, A.T., 2020. "tidyHeatmap: an R package for modular heatmap production based on tidy principles." Journal of Open Source Software. doi:10.21105/joss.02472.

Examples

```
hm =
  tidyHeatmap::N52 |>
  tidyHeatmap::heatmap(
    .row = symbol_ct,
    .column = UBR,
    .value = `read count normalised log`
  )
hm |> layer_arrow_up()
```

layer_asterisk	<i>Adds a layer of symbols above the heatmap tiles to a 'InputHeatmap', that on evaluation creates a 'ComplexHeatmap'</i>
----------------	---

Description

layer_asterisk() from a 'InputHeatmap' object, adds a symbol annotation layer over the heatmap tiles.

Usage

```
layer_asterisk(.data, ..., .size = NULL)

## S4 method for signature 'InputHeatmap'
layer_asterisk(.data, ..., .size = NULL)
```

Arguments

.data	A 'InputHeatmap'
...	Expressions that return a logical value, and are defined in terms of the variables in .data. If multiple expressions are included, they are combined with the & operator. Only rows for which all conditions evaluate to TRUE are kept.
.size	A column name or a double. The size of the elements of the layer.

Details

[Maturing]

It uses 'ComplexHeatmap' as visualisation tool.

Value

A 'InputHeatmap' object that gets evaluated to a 'ComplexHeatmap'

A 'InputHeatmap' object that gets evaluated to a 'ComplexHeatmap'

Source

[Mangiola and Papenfuss., 2020](<https://joss.theoj.org/papers/10.21105/joss.02472>)

References

Mangiola, S. and Papenfuss, A.T., 2020. "tidyHeatmap: an R package for modular heatmap production based on tidy principles." Journal of Open Source Software. doi:10.21105/joss.02472.

Examples

```

hm =
  tidyHeatmap::N52 |>
  tidyHeatmap::heatmap(
    .row = symbol_ct,
    .column = UBR,
    .value = `read count normalised log`
  )

hm |> layer_asterisk()

```

layer_diamond	<i>Adds a layers of symbols above the heatmap tiles to a ‘InputHeatmap’, that on evaluation creates a ‘ComplexHeatmap’</i>
---------------	--

Description

layer_diamond() from a ‘InputHeatmap’ object, adds a bar annotation layer.

Usage

```

layer_diamond(.data, ..., .size = NULL)

## S4 method for signature 'InputHeatmap'
layer_diamond(.data, ..., .size = NULL)

```

Arguments

.data	A ‘InputHeatmap’
...	Expressions that return a logical value, and are defined in terms of the variables in .data. If multiple expressions are included, they are combined with the & operator. Only rows for which all conditions evaluate to TRUE are kept.
.size	A column name or a double. The size of the elements of the layer.

Details**[Maturing]**

It uses ‘ComplexHeatmap’ as visualisation tool.

Value

A ‘InputHeatmap’ object that gets evaluated to a ‘ComplexHeatmap’
 A ‘InputHeatmap’ object that gets evaluated to a ‘ComplexHeatmap’

Source

[Mangiola and Papenfuss., 2020](https://joss.theoj.org/papers/10.21105/joss.02472)

References

Mangiola, S. and Papenfuss, A.T., 2020. "tidyHeatmap: an R package for modular heatmap production based on tidy principles." Journal of Open Source Software. doi:10.21105/joss.02472.

Examples

```
hm =
  tidyHeatmap::N52 |>
  tidyHeatmap::heatmap(
    .row = symbol_ct,
    .column = UBR,
    .value = `read count normalised log`
  )
hm |> layer_diamond()
```

layer_point	<i>Adds a layers of symbols above the heatmap tiles to a 'InputHeatmap', that on evaluation creates a 'ComplexHeatmap'</i>
-------------	--

Description

layer_point() from a 'InputHeatmap' object, adds a bar annotation layer.

Usage

```
layer_point(.data, ..., .size = NULL)

## S4 method for signature 'InputHeatmap'
layer_point(.data, ..., .size = NULL)
```

Arguments

.data	A 'InputHeatmap'
...	Expressions that return a logical value, and are defined in terms of the variables in .data. If multiple expressions are included, they are combined with the & operator. Only rows for which all conditions evaluate to TRUE are kept.
.size	A column name or a double. The size of the elements of the layer.

Details**[Maturing]**

It uses ‘ComplexHeatmap’ as visualisation tool.

Value

A ‘InputHeatmap’ object that gets evaluated to a ‘ComplexHeatmap’

A ‘InputHeatmap’ object that gets evaluated to a ‘ComplexHeatmap’

Source

[Mangiola and Papenfuss., 2020](<https://joss.theoj.org/papers/10.21105/joss.02472>)

References

Mangiola, S. and Papenfuss, A.T., 2020. "tidyHeatmap: an R package for modular heatmap production based on tidy principles." Journal of Open Source Software. doi:10.21105/joss.02472.

Examples

```
hm =
  tidyHeatmap::N52 |>
  tidyHeatmap::heatmap(
    .row = symbol_ct,
    .column = UBR,
    .value = `read count normalised log`
  )

hm |> layer_point()
```

layer_square	<i>Adds a layers of symbols above the heatmap tiles to a ‘InputHeatmap’, that on evaluation creates a ‘ComplexHeatmap’</i>
--------------	--

Description

layer_square() from a ‘InputHeatmap’ object, adds a bar annotation layer.

Usage

```
layer_square(.data, ..., .size = NULL)

## S4 method for signature 'InputHeatmap'
layer_square(.data, ..., .size = NULL)
```

Arguments

<code>.data</code>	A 'InputHeatmap'
<code>...</code>	Expressions that return a logical value, and are defined in terms of the variables in <code>.data</code> . If multiple expressions are included, they are combined with the <code>&</code> operator. Only rows for which all conditions evaluate to TRUE are kept.
<code>.size</code>	A column name or a double. The size of the elements of the layer.

Details**[Maturing]**

It uses 'ComplexHeatmap' as visualisation tool.

Value

A 'InputHeatmap' object that gets evaluated to a 'ComplexHeatmap'

A 'InputHeatmap' object that gets evaluated to a 'ComplexHeatmap'

Source

[Mangiola and Papenfuss., 2020](<https://joss.theoj.org/papers/10.21105/joss.02472>)

References

Mangiola, S. and Papenfuss, A.T., 2020. "tidyHeatmap: an R package for modular heatmap production based on tidy principles." Journal of Open Source Software. doi:10.21105/joss.02472.

Examples

```
hm =  
  tidyHeatmap::N52 |>  
  tidyHeatmap::heatmap(  
    .row = symbol_ct,  
    .column = UBR,  
    .value = `read count normalised log`  
  )  
  
hm |> layer_square()
```

layer_star	<i>Adds a layer of symbols above the heatmap tiles to a 'InputHeatmap', that on evaluation creates a 'ComplexHeatmap'</i>
------------	---

Description

layer_star() from a 'InputHeatmap' object, adds a symbol annotation layer over the heatmap tiles.

Usage

```
layer_star(.data, ..., .size = NULL)

## S4 method for signature 'InputHeatmap'
layer_star(.data, ..., .size = NULL)
```

Arguments

.data	A 'InputHeatmap'
...	Expressions that return a logical value, and are defined in terms of the variables in .data. If multiple expressions are included, they are combined with the & operator. Only rows for which all conditions evaluate to TRUE are kept.
.size	A column name or a double. The size of the elements of the layer.

Details

[Maturing]

It uses 'ComplexHeatmap' as visualisation tool.

Value

A 'InputHeatmap' object that gets evaluated to a 'ComplexHeatmap'

A 'InputHeatmap' object that gets evaluated to a 'ComplexHeatmap'

Source

[Mangiola and Papenfuss., 2020](<https://joss.theoj.org/papers/10.21105/joss.02472>)

References

Mangiola, S. and Papenfuss, A.T., 2020. "tidyHeatmap: an R package for modular heatmap production based on tidy principles." Journal of Open Source Software. doi:10.21105/joss.02472.

Examples

```

hm =
  tidyHeatmap::N52 |>
  tidyHeatmap::heatmap(
    .row = symbol_ct,
    .column = UBR,
    .value = `read count normalised log`
  )

hm |> layer_star()

```

layer_text	<i>Adds a layers of texts above the heatmap tiles to a 'InputHeatmap', that on evaluation creates a 'ComplexHeatmap'</i>
------------	--

Description

layer_text() from a 'InputHeatmap' object, adds a text annotation layer.

Usage

```

layer_text(.data, ..., .value, .size = NULL)

## S4 method for signature 'InputHeatmap'
layer_text(.data, ..., .value, .size = NULL)

```

Arguments

.data	A 'InputHeatmap'
...	Expressions that return a logical value, and are defined in terms of the variables in .data. If multiple expressions are included, they are combined with the & operator. Only rows for which all conditions evaluate to TRUE are kept.
.value	A column name or character string.
.size	A column name or a double. The size of the elements of the layer.

Details**[Maturing]**

It uses 'ComplexHeatmap' as visualisation tool.

Value

A 'InputHeatmap' object that gets evaluated to a 'ComplexHeatmap'
 A 'InputHeatmap' object that gets evaluated to a 'ComplexHeatmap'

Source

[Mangiola and Papenfuss., 2020](<https://joss.theoj.org/papers/10.21105/joss.02472>)

References

Mangiola, S. and Papenfuss, A.T., 2020. "tidyHeatmap: an R package for modular heatmap production based on tidy principles." *Journal of Open Source Software*. doi:10.21105/joss.02472.

Examples

```
library(dplyr)

hm =
  tidyHeatmap::N52 |>
  mutate(my_text = "t") |>
  tidyHeatmap::heatmap(
    .row = symbol_ct,
    .column = UBR,
    .value = `read count normalised log`
  )

hm |> layer_text(.value = "a")
hm |> layer_text(.value = my_text)
```

N52

Example data set N52

Description

Example data set N52

Usage

N52

Format

An object of class `tbl_df` (inherits from `tbl`, `data.frame`) with 520 rows and 15 columns.

Source

[Mangiola and Papenfuss., 2020](<https://joss.theoj.org/papers/10.21105/joss.02472>)

References

Mangiola, S. and Papenfuss, A.T., 2020. "tidyHeatmap: an R package for modular heatmap production based on tidy principles." *Journal of Open Source Software*. doi:10.21105/joss.02472.

parse_formula	<i>.formula parser</i>
---------------	------------------------

Description

.formula parser

Usage

```
parse_formula(fm)
```

Arguments

fm a formula

Value

A character vector

pasilla	<i>Example data set Pasilla</i>
---------	---------------------------------

Description

Example data set Pasilla

Usage

```
pasilla
```

Format

An object of class `tbl_df` (inherits from `tbl`, `data.frame`) with 504 rows and 8 columns.

Source

[Mangiola and Papenfuss., 2020](<https://joss.theoj.org/papers/10.21105/joss.02472>)

References

Mangiola, S. and Papenfuss, A.T., 2020. "tidyHeatmap: an R package for modular heatmap production based on tidy principles." *Journal of Open Source Software*. doi:10.21105/joss.02472.

```
prepend
```

From rlang deprecated

Description

From rlang deprecated

Usage

```
prepend(x, values, before = 1)
```

Arguments

x	An array
values	An array
before	A boolean

Value

An array

```
quo_names
```

Convert array of quosure (e.g. c(col_a, col_b)) into character vector

Description

Convert array of quosure (e.g. c(col_a, col_b)) into character vector

Usage

```
quo_names(v)
```

Arguments

v	A array of quosures (e.g. c(col_a, col_b))
---	--

Value

A character vector

save_pdf	<i>Save plot on PDF file</i>
----------	------------------------------

Description

save_pdf() takes as input a Heatmap from ComplexHeatmap and save it to PDF file

Usage

```
save_pdf(  
  .heatmap,  
  filename,  
  width = NULL,  
  height = NULL,  
  units = c("in", "cm", "mm")  
)
```

Arguments

.heatmap	A 'Heatmap'
filename	A character string. The name of the output file/path
width	A 'double'. Plot width
height	A 'double'. Plot height
units	A character string. units ("in", "cm", or "mm")

Details

[Maturing]

It simply save an 'Heatmap' to a PDF file use pdf() function in the back end

Value

NA

Source

[Mangiola and Papenfuss., 2020](<https://joss.theoj.org/papers/10.21105/joss.02472>)

References

Mangiola, S. and Papenfuss, A.T., 2020. "tidyHeatmap: an R package for modular heatmap production based on tidy principles." Journal of Open Source Software. doi:10.21105/joss.02472.

Examples

```
tidyHeatmap::heatmap(  
  dplyr::group_by(tidyHeatmap::pasilla, location, type),  
  .column = sample,  
  .row = symbol,  
  .value = `count normalised adjusted`,  
) |>  
save_pdf(tempfile())
```

save_pdf,Heatmap-method

save_pdf

Description

save_pdf

Usage

```
## S4 method for signature 'Heatmap'  
save_pdf(  
  .heatmap,  
  filename,  
  width = NULL,  
  height = NULL,  
  units = c("in", "cm", "mm")  
)
```

Arguments

.heatmap	A 'Heatmap'
filename	A character string. The name of the output file/path
width	A 'double'. Plot width
height	A 'double'. Plot height
units	A character string. units ("in", "cm", or "mm")

```
save_pdf, InputHeatmap-method
      save_pdf
```

Description

save_pdf

Usage

```
## S4 method for signature 'InputHeatmap'
save_pdf(
  .heatmap,
  filename,
  width = NULL,
  height = NULL,
  units = c("in", "cm", "mm")
)
```

Arguments

.heatmap	A 'Heatmap'
filename	A character string. The name of the output file/path
width	A 'double'. Plot width
height	A 'double'. Plot height
units	A character string. units ("in", "cm", or "mm")

```
scale_robust      Scale counts in a robust way against sd == 0
```

Description

Scale counts in a robust way against $sd == 0$

Usage

```
scale_robust(y)
```

Arguments

y	A numerical array
---	-------------------

Value

A scaled and centred numerical array

Source

[Mangiola and Papenfuss., 2020](https://joss.theoj.org/papers/10.21105/joss.02472)

References

Mangiola, S. and Papenfuss, A.T., 2020. "tidyHeatmap: an R package for modular heatmap production based on tidy principles." Journal of Open Source Software. doi:10.21105/joss.02472.

select_closest_pairs *Sub function of remove_redundancy_elements_though_reduced_dimensions*

Description

Sub function of remove_redundancy_elements_though_reduced_dimensions

Usage

```
select_closest_pairs(df)
```

Arguments

df A tibble

Value

A tibble with pairs to drop

split_rows *Split the heatmap row-wise depending on the biggest branches in the cladogram.*

Description

split_rows() from a 'InputHeatmap' object, split the row cladogram.

split_columns() from a 'InputHeatmap' object, split the column cladogram.

Usage

```
split_rows(.data, number_of_groups)
```

```
## S4 method for signature 'InputHeatmap'
split_rows(.data, number_of_groups)
```

```
split_columns(.data, number_of_groups)
```

```
## S4 method for signature 'InputHeatmap'
split_columns(.data, number_of_groups)
```

Arguments

`.data` A 'InputHeatmap'
`number_of_groups` An integer. The number of groups to split the cladogram into.

Details**[Maturing]**

It uses 'ComplexHeatmap' as visualisation tool.

[Maturing]

It uses 'ComplexHeatmap' as visualisation tool.

Value

A 'InputHeatmap' object that gets evaluated to a 'ComplexHeatmap'

A 'InputHeatmap' object that gets evaluated to a 'ComplexHeatmap'

A 'InputHeatmap' object that gets evaluated to a 'ComplexHeatmap'

A 'InputHeatmap' object that gets evaluated to a 'ComplexHeatmap'

Source

[Mangiola and Papenfuss., 2020](<https://joss.theoj.org/papers/10.21105/joss.02472>)

[Mangiola and Papenfuss., 2020](<https://joss.theoj.org/papers/10.21105/joss.02472>)

References

Mangiola, S. and Papenfuss, A.T., 2020. "tidyHeatmap: an R package for modular heatmap production based on tidy principles." Journal of Open Source Software. doi:10.21105/joss.02472.

Mangiola, S. and Papenfuss, A.T., 2020. "tidyHeatmap: an R package for modular heatmap production based on tidy principles." Journal of Open Source Software. doi:10.21105/joss.02472.

Examples

```
hm =
  tidyHeatmap::N52 |>
  tidyHeatmap::heatmap(
    .row = symbol_ct,
    .column = UBR,
    .value = `read count normalised log`
  )
```

```
hm |> split_rows(2)
```

```
hm =
```

```

tidyHeatmap::N52 |>
tidyHeatmap::heatmap(
  .row = symbol_ct,
  .column = UBR,
  .value = `read count normalised log`
)

hm |> split_columns(2)

```

wrap_heatmap	<i>Wrap tidyHeatmap (ComplexHeatmap) in a patchwork-compliant patch</i>
--------------	---

Description

In order to add tidyHeatmap (ComplexHeatmap) element to a patchwork they can be converted to a compliant representation using the 'wrap_heatmap()' function. This allows you to position either grobs, ggplot objects, patchwork objects, or even base graphics (if passed as a formula) in either the full area, the full plotting area (anything between and including the axis label), or the panel area (only the actual area where data is drawn).

Usage

```

wrap_heatmap(
  panel = NULL,
  plot = NULL,
  full = NULL,
  clip = TRUE,
  ignore_tag = FALSE,
  padding = NULL
)

## S4 method for signature 'InputHeatmap'
wrap_heatmap(
  panel = NULL,
  plot = NULL,
  full = NULL,
  clip = TRUE,
  ignore_tag = FALSE,
  padding = NULL
)

```

Arguments

panel, plot, full

A grob, ggplot, patchwork, formula, raster, or nativeRaster object to add to the respective area.

clip	Should the grobs be clipped if expanding outside its area
ignore_tag	Should tags be ignored for this patch. This is relevant when using automatic tagging of plots and the content of the patch does not qualify for a tag.
padding	A <code>grid::unit</code> object. It defined the padding distance for the plot. It is helpful when the heatmap is assembled with other ggplots through patchwork.

Value

A `wrapped_patch` object

A `wrapped_patch` object

Source

[Mangiola and Papenfuss., 2020](<https://joss.theoj.org/papers/10.21105/joss.02472>)

References

Mangiola, S. and Papenfuss, A.T., 2020. "tidyHeatmap: an R package for modular heatmap production based on tidy principles." *Journal of Open Source Software*. doi:10.21105/joss.02472.

Examples

```
tidyHeatmap::N52 |>
tidyHeatmap::heatmap(
  .row = symbol_ct,
  .column = UBR,
  .value = `read count normalised log`,
) |>
wrap_heatmap()
```

Index

- * **datasets**
 - N52, [40](#)
 - pasilla, [41](#)

- [add_annotation](#), [3](#)
- [add_attr](#), [4](#)
- [add_bar](#), [5](#)
- [add_bar](#), [InputHeatmap-method \(add_bar\)](#), [5](#)
- [add_class](#), [6](#)
- [add_line](#), [7](#)
- [add_line](#), [InputHeatmap-method \(add_line\)](#), [7](#)
- [add_point](#), [8](#)
- [add_point](#), [InputHeatmap-method \(add_point\)](#), [8](#)
- [add_tile](#), [9](#)
- [add_tile](#), [InputHeatmap-method \(add_tile\)](#), [9](#)
- [anno_barplot](#), [10](#)
- [anno_block](#), [16](#)
- [anno_lines](#), [11](#)
- [anno_numeric](#), [13](#)
- [anno_points](#), [14](#)
- [annot_to_list](#), [17](#)
- [annotation_bar](#), [10](#)
- [annotation_bar](#), [InputHeatmap-method \(annotation_bar\)](#), [10](#)
- [annotation_line](#), [11](#)
- [annotation_line](#), [InputHeatmap-method \(annotation_line\)](#), [11](#)
- [annotation_numeric](#), [12](#)
- [annotation_numeric](#), [InputHeatmap-method \(annotation_numeric\)](#), [12](#)
- [annotation_point](#), [14](#)
- [annotation_point](#), [InputHeatmap-method \(annotation_point\)](#), [14](#)
- [annotation_tile](#), [15](#)
- [annotation_tile](#), [InputHeatmap-method \(annotation_tile\)](#), [15](#)
- [as_ComplexHeatmap](#), [17](#)

- [as_ComplexHeatmap](#), [InputHeatmap-method \(as_ComplexHeatmap\)](#), [17](#)
- [as_matrix](#), [18](#)

- [check_if_counts_is_na](#), [19](#)
- [check_if_duplicated_genes](#), [19](#)
- [check_if_wrong_input](#), [20](#)

- [drop_class](#), [20](#)

- [error_if_log_transformed](#), [21](#)

- [get_abundance_norm_if_exists](#), [21](#)
- [get_elements](#), [22](#)
- [get_elements_features](#), [22](#)
- [get_elements_features_abundance](#), [23](#)
- [get_sample_counts](#), [23](#)
- [get_sample_transcript](#), [24](#)
- [get_sample_transcript_counts](#), [24](#)
- [get_x_y_annotation_columns](#), [25](#)

- [heatmap](#), [25](#)
- [heatmap](#), [tbl-method \(heatmap\)](#), [25](#)
- [heatmap](#), [tbl_df-method \(heatmap\)](#), [25](#)
- [heatmap_](#) ([heatmap](#)), [25](#)
- [HeatmapAnnotation](#), [10](#), [11](#), [13](#), [14](#), [16](#)

- [ifelse2_pipe](#), [28](#)
- [ifelse_pipe](#), [28](#)
- [input_heatmap](#), [29](#)

- [layer_arrow_down](#), [30](#)
- [layer_arrow_down](#), [InputHeatmap-method \(layer_arrow_down\)](#), [30](#)
- [layer_arrow_up](#), [31](#)
- [layer_arrow_up](#), [InputHeatmap-method \(layer_arrow_up\)](#), [31](#)
- [layer_asterisk](#), [33](#)
- [layer_asterisk](#), [InputHeatmap-method \(layer_asterisk\)](#), [33](#)
- [layer_diamond](#), [34](#)

layer_diamond, InputHeatmap-method
 (layer_diamond), 34

layer_point, 35

layer_point, InputHeatmap-method
 (layer_point), 35

layer_square, 36

layer_square, InputHeatmap-method
 (layer_square), 36

layer_star, 38

layer_star, InputHeatmap-method
 (layer_star), 38

layer_text, 39

layer_text, InputHeatmap-method
 (layer_text), 39

N52, 40

parse_formula, 41

pasilla, 41

prepend, 42

quo_names, 42

save_pdf, 43

save_pdf, Heatmap-method, 44

save_pdf, InputHeatmap-method, 45

scale_robust, 45

select_closest_pairs, 46

split_columns (split_rows), 46

split_columns, InputHeatmap-method
 (split_rows), 46

split_rows, 46

split_rows, InputHeatmap-method
 (split_rows), 46

wrap_heatmap, 48

wrap_heatmap, InputHeatmap-method
 (wrap_heatmap), 48