

Package: treeSS (via r-universe)

May 30, 2026

Type Package

Title Tree-Spatial Scan Statistic for Cluster Detection

Version 0.1.50

Description Implements the tree-spatial scan statistic for detecting clusters that combine both spatial and hierarchical structures, as proposed by Cancado et al. (2025) <[doi:10.1007/s10651-025-00670-w](https://doi.org/10.1007/s10651-025-00670-w)>. The method extends Kulldorff (1997) <[doi:10.1080/03610929708831995](https://doi.org/10.1080/03610929708831995)> circular spatial scan statistic and the tree-based scan statistic of Kulldorff et al. (2003) <[doi:10.1111/1541-0420.00039](https://doi.org/10.1111/1541-0420.00039)> by searching for anomalies in both geographic regions and branches of hierarchical trees simultaneously. The package also provides standalone implementations of Kulldorff's circular spatial scan statistic and the tree-based scan statistic. Statistical significance is assessed via Monte Carlo simulation under a Poisson or binomial model, with optional 'OpenMP' parallelization.

License GPL (>= 3)

URL <https://github.com/allanvc/treeSS>

BugReports <https://github.com/allanvc/treeSS/issues>

Depends R (>= 3.5.0)

Imports Rcpp (>= 1.0.0), stats

LinkingTo Rcpp

Suggests testthat (>= 3.0.0), knitr, rmarkdown, sf

SystemRequirements GNU make

Encoding UTF-8

LazyData true

LazyDataCompression xz

VignetteBuilder knitr

RoxygenNote 7.3.2

Config/testthat/edition 3

NeedsCompilation yes

Author Allan Quadros [aut, cre] (ORCID:
<https://orcid.org/0000-0003-3250-5380>), Andre L. F. Cançado
 [aut] (ORCID: <https://orcid.org/0000-0002-7019-8521>),
 Geiziane S. Oliveira [aut], Luiz H. Duczmal [aut]

Maintainer Allan Quadros <allanvcq@gmail.com>

Config/pak/sysreqs make

Repository <https://cran.r-universe.dev>

Date/Publication 2026-05-30 04:31:00 UTC

RemoteUrl <https://github.com/cran/treeSS>

RemoteRef HEAD

RemoteSha 77d049f544ac9695f5190b792d0828282e4850ef

Contents

| | |
|------------------------------------|----|
| treeSS-package | 3 |
| aggregate_tree | 4 |
| build_zones | 5 |
| chicago_crimes | 6 |
| chicago_map | 8 |
| chicago_tree | 8 |
| circular_scan | 9 |
| filter_clusters | 11 |
| fl_deaths | 12 |
| generate_example_data | 13 |
| get_cluster_regions | 14 |
| london_boroughs_map | 16 |
| london_collisions | 17 |
| london_tree | 18 |
| print.circular_scan | 19 |
| print.sequential_scan | 19 |
| print.tree_scan | 20 |
| print.treespatial_scan | 21 |
| rj_mortality | 21 |
| rj_tree | 23 |
| sequential_scan | 24 |
| summary.circular_scan | 26 |
| summary.sequential_scan | 27 |
| summary.tree_scan | 27 |
| summary.treespatial_scan | 28 |
| tree_scan | 29 |
| treespatial_scan | 30 |

Index

33

treeSS-package

treeSS: Tree-Spatial Scan Statistic for Cluster Detection

Description

Implements the tree-spatial scan statistic for detecting clusters that combine both spatial and hierarchical structures, as proposed by Cançado et al. (2025). The method extends Kulldorff's (1997) circular spatial scan statistic and the tree-based scan statistic (Kulldorff et al. 2003) by searching for anomalies in both geographic regions and branches of hierarchical trees simultaneously.

Main functions

`treespacial_scan` Performs the tree-spatial scan statistic, detecting clusters defined by pairs of spatial zones and tree branches.

`circular_scan` Performs Kulldorff's circular spatial scan statistic.

`tree_scan` Performs the tree-based scan statistic.

Helper functions

`build_zones` Constructs candidate spatial zones using circular windows centered on region centroids.

`aggregate_tree` Aggregates case counts from leaves to internal nodes of the hierarchical tree.

`filter_clusters` Removes overlapping secondary clusters from a single-pass scan output (Cançado et al. 2025, Sec. 5.1.1).

`sequential_scan` Sequential adjustment for secondary clusters: removes the most likely cluster's regions and re-runs the scan with a fresh Monte Carlo simulation (Zhang, Assunção & Kulldorff 2010).

`get_cluster_regions` Returns a tidy region-by-cluster data.frame suitable for plotting with any mapping package.

Author(s)

Maintainer: Allan Quadros <allanvcq@gmail.com> ([ORCID](#))

Authors:

- Andre L. F. Cancado ([ORCID](#))
- Geiziane S. Oliveira
- Luiz H. Duczmal

References

- Cançado, A. L. F., Oliveira, G. S., Quadros, A. V. C., & Duczmal, L. (2025). A tree-spatial scan statistic. *Environmental and Ecological Statistics*, 32, 953–978. doi:10.1007/s1065102500670w
- Kulldorff, M. (1997). A spatial scan statistic. *Communications in Statistics - Theory and Methods*, 26(6), 1481–1496.
- Kulldorff, M., Fang, Z., & Walsh, S. J. (2003). A tree-based scan statistic for database disease surveillance. *Biometrics*, 59(2), 323–331.
- Zhang, Z., Assunção, R., & Kulldorff, M. (2010). Spatial scan statistics adjusted for multiple clusters. *Journal of Probability and Statistics*, 2010, 642379.

See Also

Useful links:

- <https://github.com/allanvc/treeSS>
- Report bugs at <https://github.com/allanvc/treeSS/issues>

| | |
|----------------|--|
| aggregate_tree | <i>Aggregate Case Counts from Leaves to All Nodes in a Hierarchical Tree</i> |
|----------------|--|

Description

Given case counts at the leaf level (as parallel vectors) and a tree, aggregates case counts upward from child nodes to parent nodes, producing a complete case matrix indexed by all nodes (rows) and regions (columns).

Usage

```
aggregate_tree(
  cases,
  region_id,
  node_id,
  tree = NULL,
  tree_node_id = NULL,
  tree_parent_id = NULL
)
```

Arguments

| | |
|------------------------------|---|
| cases | Numeric vector of length n : case counts. |
| region_id | Vector of region identifiers, length n . |
| node_id | Vector of leaf identifiers, length n . |
| tree | A data.frame with columns node_id and parent_id. As an alternative, pass tree_node_id and tree_parent_id. |
| tree_node_id, tree_parent_id | Optional. Parallel vectors as an alternative to tree. |

Details

This function is exposed for inspection and pedagogical use; the scan functions call it internally on the matrix they build from your input vectors.

Value

A matrix of dimensions $m \times k$ (nodes x regions), with rows ordered by `tree$node_id` and columns by region.

References

Cancado, A. L. F., Oliveira, G. S., Quadros, A. V. C., & Duczmal, L. (2025). A tree-spatial scan statistic. *Environmental and Ecological Statistics*, 32, 953-978. doi:10.1007/s1065102500670w

Examples

```
tree <- data.frame(
  node_id = c(1, 2, 3, 4, 5, 6, 7),
  parent_id = c(NA, 1, 1, 2, 2, 3, 3)
)
# Leaves are 4, 5, 6, 7
aggregate_tree(
  cases = c(10, 5, 3, 8, 2, 7, 4, 1, 6, 3, 9, 2),
  region_id = rep(1:3, each = 4),
  node_id = rep(c(4, 5, 6, 7), times = 3),
  tree = tree
)
```

 build_zones

Build Candidate Spatial Zones Using Circular Windows

Description

Constructs the set of candidate spatial zones for the circular scan statistic. Each zone is defined by a circular window centered on a region's centroid, containing all regions whose centroids fall within the circle.

Usage

```
build_zones(regions, max_pop = NULL)
```

Arguments

| | |
|----------------------|--|
| <code>regions</code> | A data.frame with columns <code>region_id</code> , <code>population</code> , <code>x</code> , and <code>y</code> . Coordinates <code>x</code> and <code>y</code> represent centroids of each region. |
| <code>max_pop</code> | A numeric value specifying the maximum population allowed inside a zone. If NULL (default), it is set to 50% of the total population. |

Details

For each region j , regions are sorted by distance from j . Regions are added incrementally to the zone as long as the total population does not exceed `max_pop`. This generates a nested set of circular windows centered on each region.

Value

A list of zones. Each zone is a list with elements:

center Integer index of the center region.

region_idx Integer vector of region indices inside the zone.

population Total population inside the zone.

References

Kulldorff, M. (1997). A spatial scan statistic. *Communications in Statistics - Theory and Methods*, 26(6), 1481–1496.

Examples

```
regions <- data.frame(
  region_id = 1:5,
  population = c(1000, 2000, 1500, 800, 1200),
  x = c(0, 1, 2, 0.5, 1.5),
  y = c(0, 0, 0, 1, 1)
)
zones <- build_zones(regions, max_pop = 3000)
length(zones) # number of candidate zones
```

chicago_crimes

Chicago Crime (2023)

Description

Combined long-format dataset of crime incidents in the 77 community areas of Chicago, 2023. Use together with [chicago_tree](#).

Usage

chicago_crimes

Format

A data.frame in long format with columns:

region_id Integer identifier of the community area.

area_number Official community area number (1–77).

name Community area name.

population Total incidents in the area. This is a compositional denominator (sums to the total incident count of the city) and is useful for analyses that ask "which crime types over-occur in which areas relative to the citywide profile". Not a population at risk.

pop_residential Residential population of the community area. Use this as the denominator for incidence-rate analyses (incidents per resident). Source: U.S. Census Bureau, ACS 2020 5-year estimates, aggregated to community areas by CMAP Community Data Snapshots. The 77 values sum to approximately 2.71M, matching the published Chicago population.

x Longitude of the centroid.

y Latitude of the centroid.

node_id Character leaf identifier from [chicago_tree](#).

cases Integer count of crime incidents.

Source

Crime incidents: City of Chicago Data Portal, Crimes – 2001 to Present.

Residential population: U.S. Census Bureau ACS 2020 5-year estimates, aggregated to community areas by the Chicago Metropolitan Agency for Planning (CMAP), Community Data Snapshots (2023 release). <https://cmap.illinois.gov/data/community-data-snapshots/>

See Also

[chicago_tree](#), [chicago_map](#)

Examples

```
data(chicago_crimes)
head(chicago_crimes)
cat("Total incidents:", sum(chicago_crimes$cases), "\n")
cat("Total residents:",
    sum(unique(chicago_crimes[, c("area_number", "pop_residential")])$pop_residential),
    "\n")
```

`chicago_map`*Chicago Community Area Boundaries*

Description

Simplified polygon boundaries for the 77 community areas in Chicago.

Format

An sf data.frame with 77 rows and 3 columns:

NAME Community area name.

AREA_NUM Community area number (integer, 1–77).

geometry MULTIPOLYGON geometry in WGS84 (EPSG:4326).

Source

City of Chicago Data Portal, Community Area Boundaries.

See Also

[chicago_crimes](#)

Examples

```
data(chicago_map)
cat("Community areas:", nrow(chicago_map), "\n")
```

`chicago_tree`*Chicago Crime - Hierarchy*

Description

Hierarchical classification of crime incidents by type, description and location group.

Usage

```
chicago_tree
```

Format

A data.frame with 2,841 rows and 2 columns:

node_id Character identifier of each node.

parent_id Character identifier of the parent node. NA for the root.

Details

4-level tree: Root -> Crime Type -> Description -> Location Group. 2,486 leaf nodes. Leaf node IDs follow the pattern "<TYPE> | <DESCRIPTION> | <LOCATION>".

Source

Constructed from the leaf-level codes in [chicago_crimes](#). See data-raw/ in the GitHub repository for the build script.

See Also

[chicago_crimes](#)

Examples

```
data(chicago_tree)
head(chicago_tree)
```

circular_scan

Kulldorff's Circular Spatial Scan Statistic

Description

Performs Kulldorff's circular spatial scan statistic for detecting spatial clusters. Inputs are passed as parallel vectors with one entry per region (cases must already be aggregated to the region level).

Usage

```
circular_scan(
  cases,
  population,
  region_id,
  x,
  y,
  max_pop_pct = 0.5,
  nsim = 999L,
  alpha = 0.05,
  n_secondary = 1000L,
  model = c("poisson", "binomial"),
  seed = NULL,
  n_cores = 1L
)
```

Arguments

| | |
|-------------|--|
| cases | Numeric vector of length n (one entry per region): total cases in each region. |
| population | Numeric vector of length n : population (or denominator) of each region. |
| region_id | Vector of region identifiers, length n . |
| x, y | Numeric vectors of region centroid coordinates, length n . |
| max_pop_pct | Numeric. Default 0.5. |
| nsim | Integer. Number of MC simulations. Default 999. |
| alpha | Numeric. Significance level. Default 0.05. |
| n_secondary | Integer. Default 1000. |
| model | Character. "poisson" or "binomial". |
| seed | Integer or NULL. Random seed for the Monte Carlo loop. When non-NULL, the user's pre-existing RNG state is saved on entry and restored on exit, so the seed argument affects only this call and does not leak into subsequent draws in the user's session. |
| n_cores | Integer. OpenMP threads. |

Value

An object of class "circular_scan".

References

Kulldorff, M. (1997). A spatial scan statistic. *Communications in Statistics - Theory and Methods*, 26(6), 1481-1496.

See Also

[filter_clusters](#), [tree_scan](#), [treespatial_scan](#), [get_cluster_regions](#), [sequential_scan](#)

Examples

```
set.seed(42)
n <- 20
cases <- rpois(n, lambda = 10)
cases[1:5] <- rpois(5, lambda = 30)

result <- circular_scan(
  cases      = cases,
  population = rep(1000, n),
  region_id  = 1:n,
  x          = runif(n, 0, 10),
  y          = runif(n, 0, 10),
  nsim       = 99
)
print(result)
```

filter_clusters *Filter Overlapping Secondary Clusters*

Description

Removes overlapping secondary clusters from the output of [treespatial_scan](#), [circular_scan](#), or [tree_scan](#).

Usage

```
filter_clusters(result, alpha = NULL)
```

Arguments

| | |
|--------|---|
| result | An object of class "treespatial_scan", "circular_scan", or "tree_scan". |
| alpha | Numeric. Significance level. Default is NULL (uses alpha from the original analysis). |

Details

treespatial_scan: two clusters overlap if they have BOTH tree overlap (ancestor/descendant) AND spatial overlap (same center or identical regions). Follows Cancado et al. (2025).

circular_scan: Kulldorff (1997) criterion — center of candidate not in any retained zone, and no retained center in the candidate zone.

tree_scan: a secondary cluster is distinct if its node is NOT an ancestor or descendant of any previously retained node. Follows Kulldorff et al. (2003).

Value

A data frame of distinct significant clusters ordered by descending LLR.

References

- Kulldorff, M. (1997). A spatial scan statistic. *Communications in Statistics*, 26(6), 1481-1496.
- Kulldorff, M., Fang, Z., & Walsh, S. J. (2003). A tree-based scan statistic for database disease surveillance. *Biometrics*, 59(2), 323-331.
- Cancado, A. L. F., Oliveira, G. S., Quadros, A. V. C., & Duczmal, L. (2025). A tree-spatial scan statistic. *Environmental and Ecological Statistics*, 32, 953–978. doi:10.1007/s1065102500670w

See Also

[treespatial_scan](#), [circular_scan](#), [tree_scan](#), [sequential_scan](#)

Examples

```
data(london_collisions); data(london_tree)
result <- treespatial_scan(
  cases      = london_collisions$cases,
  population = london_collisions$population,
  region_id  = london_collisions$region_id,
  x          = london_collisions$x,
  y          = london_collisions$y,
  node_id    = london_collisions$node_id,
  tree       = london_tree,
  nsim       = 99, seed = 42
)
filter_clusters(result)
```

fl_deaths

Florida General Mortality Data (2016)

Description

Death counts by county and ICD-10 cause of death for the state of Florida, USA, 2016. This is **raw data** – the user builds the ICD-10 tree and cases matrix in the analysis script, making it a pedagogical example of the full workflow.

Format

A data.frame with 3,066 rows and 6 columns:

county_fips 5-digit FIPS code (character), e.g. "12086".

county_name County name, e.g. "Miami-Dade County".

icd10_code ICD-10 cause of death code, e.g. "I25.1".

icd10_desc Description of the ICD-10 code, e.g. "Atherosclerotic heart disease".

deaths Number of deaths (integer).

population County population estimate (integer).

Details

Covers 65 of Florida's 67 counties, 253 ICD-10 codes, and 157,000 total deaths. All ages, all causes.

County polygons and centroids can be obtained via `tigris::counties(state = "FL", cb = TRUE)`.

The ICD-10 descriptions in `icd10_desc` can be used to build a lookup table: `unique(fl_deaths[, c("icd10_code", "icd10_desc")])`.

Source

CDC WONDER Compressed Mortality File 1999–2016 (<https://wonder.cdc.gov/cmfi-icd10.html>).

Examples

```
data(fl_deaths)
head(fl_deaths)
cat("Counties:", length(unique(fl_deaths$county_fips)), "\n")
cat("ICD-10 codes:", length(unique(fl_deaths$icd10_code)), "\n")
cat("Total deaths:", sum(fl_deaths$deaths), "\n")
```

generate_example_data *Generate Example Data for Tree-Spatial Scan*

Description

Creates a synthetic dataset for demonstrating and testing the tree-spatial scan statistic. Returns parallel vectors (cases, population, region_id, x, y, node_id) and a tree, matching the input format expected by [treespatial_scan](#).

Usage

```
generate_example_data(
  n_regions = 50L,
  pop_per_region = 1000,
  cluster_regions = 1:7,
  cluster_leaves = c(3, 4),
  rr = 2,
  Cg = 200L,
  seed = NULL
)
```

Arguments

| | |
|-----------------|---|
| n_regions | Integer. Default 50. |
| pop_per_region | Numeric. Default 1000. |
| cluster_regions | Integer vector. Default 1:7. |
| cluster_leaves | Integer vector. Default c(3, 4). |
| rr | Numeric. Relative risk. Default 2.0. |
| Cg | Integer. Cases per branch. Default 200. |
| seed | Integer or NULL. Random seed. When non-NULL, the user's pre-existing RNG state is saved on entry and restored on exit, so the seed argument affects only the result of the call. Default NULL (the user's session-level RNG state is used as-is and is not modified by the function). |

Value

A list with vector components ready to feed into [treespatial_scan](#): cases, population, region_id, x, y, node_id, plus the tree (data.frame) and a true_cluster list describing the injected cluster.

Examples

```

ex <- generate_example_data(seed = 42)
result <- treespatial_scan(
  cases      = ex$cases,
  population = ex$population,
  region_id  = ex$region_id,
  x          = ex$x,
  y          = ex$y,
  node_id    = ex$node_id,
  tree       = ex$tree,
  nsim       = 99
)
print(result)

```

get_cluster_regions *Extract Cluster Membership for Each Region*

Description

Returns a data.frame indicating which cluster (if any) each region belongs to. This is the primary output for visualization — use it with any mapping package (ggplot2, leaflet, tmap, etc.).

Usage

```

get_cluster_regions(result, n_clusters = 1L, overlap = TRUE, ...)

## Default S3 method:
get_cluster_regions(result, n_clusters = 1L, overlap = TRUE, ...)

## S3 method for class 'sequential_scan'
get_cluster_regions(result, n_clusters = 1L, overlap = TRUE, ...)

```

Arguments

| | |
|------------|--|
| result | A "treespatial_scan" or "circular_scan" object (single-pass scan), or a "sequential_scan" object (Zhang, Assuncao and Kulldorff, 2010). |
| n_clusters | Integer. (Single-pass methods only.) Number of clusters to extract. 1 returns only the most likely cluster. Values greater than 1 use filter_clusters internally to identify distinct secondary clusters. Default is 1. Ignored for sequential scan inputs (all detected iterations are returned). |
| overlap | Logical. If TRUE (default), returns a facet-ready data.frame: all regions are replicated for each cluster panel, with a panel column for faceting and cluster marked only for member regions. If FALSE, returns one row per region assigned to its highest-ranked cluster (for single-panel maps). |
| ... | Further arguments passed to methods. |

Details

This is a generic with methods for objects returned by [treespatial_scan](#), [circular_scan](#), and [sequential_scan](#).

Value

A data.frame with columns from `result$regions` plus:

cluster Integer cluster number (1 = most likely / first iteration, 2 = first secondary / second iteration, etc.), or NA if the region is not in the cluster.

node_id The tree node of the cluster, or NA.

llr The log-likelihood ratio of the cluster, or NA.

pvalue The p-value of the cluster, or NA.

panel (Only when `overlap = TRUE`) A two-line label for `facet_wrap`, with the cluster identifier on the first line and the test statistic on the second. For single-pass scans the label looks like `"#1 P209\n(LR=39.6)";` for sequential scans it looks like `"Iter 1: P209\n(LR=39.6, p=0.005)";`. The newline keeps long node identifiers from overflowing the strip in multi-panel layouts.

See Also

[treespatial_scan](#), [circular_scan](#), [sequential_scan](#), [filter_clusters](#)

Examples

```
data(london_collisions); data(london_tree)
result <- treespatial_scan(
  cases      = london_collisions$cases,
  population = london_collisions$population,
  region_id  = london_collisions$region_id,
  x          = london_collisions$x,
  y          = london_collisions$y,
  node_id    = london_collisions$node_id,
  tree       = london_tree,
  nsim       = 99, seed = 42
)

# Long format suitable for merging with a polygon layer.
cr <- get_cluster_regions(result, n_clusters = 2L, overlap = TRUE)
head(cr)
```

london_boroughs_map *London Borough Boundaries*

Description

Simplified polygon boundaries for the 33 London boroughs. Use with [london_collisions](#) for map-based visualization of cluster results.

Format

An sf data.frame with 33 rows and 3 columns:

NAME Borough name, e.g. "Westminster".

GSS_CODE ONS geography code, e.g. "E09000033".

geometry MULTIPOLYGON geometry in WGS84 (EPSG:4326).

Details

Geometries are simplified (`st_simplify(dTolerance = 0.001)`) to reduce file size. For full-resolution boundaries, download from the source URL.

To merge with cluster results from [get_cluster_regions](#), use: `merge(london_boroughs_map, cr, by.x = "NAME", by.y = "borough")`.

Source

London Datastore, Statistical GIS Boundary Files for London (see <https://data.london.gov.uk/dataset/statistical-gis-boundary-files-london/>). Contains National Statistics data (c) Crown copyright and database right 2014.

See Also

[london_collisions](#)

Examples

```
data(london_boroughs_map)
cat("Boroughs:", nrow(london_boroughs_map), "\n")
```

| | |
|-------------------|--------------------------------------|
| london_collisions | <i>London Road Collisions (2022)</i> |
|-------------------|--------------------------------------|

Description

Combined long-format dataset of road traffic collisions in the 33 London boroughs, 2022. Each row represents a (borough, collision-category) combination with at least one collision. Use together with [london_tree](#).

Usage

```
london_collisions
```

Format

A data.frame in long format with columns:

region_id Integer identifier of the borough.

borough Borough name.

population Total collisions in the borough (used as population denominator).

x Longitude of the borough centroid.

y Latitude of the borough centroid.

node_id Character leaf identifier from [london_tree](#).

cases Integer count of collisions.

Source

UK Department for Transport, STATS19 data via the stats19 R package.

See Also

[london_tree](#), [london_boroughs_map](#)

Examples

```
data(london_collisions)
head(london_collisions)
cat("Total collisions:", sum(london_collisions$cases), "\n")
```

| | |
|-------------|---|
| london_tree | <i>London Road Collisions - Hierarchy</i> |
|-------------|---|

Description

Hierarchical classification of road collisions by light conditions, road type, and junction detail.

Usage

```
london_tree
```

Format

A data.frame with 81 rows and 2 columns:

node_id Character identifier of each node.

parent_id Character identifier of the parent node. NA for the root.

Details

3-level tree: Root -> Light conditions (Daylight/Darkness) -> Road type (5 types) -> Junction detail (7 types). 68 leaf categories.

Source

Constructed from the leaf-level codes in [london_collisions](#). See data-raw/ in the GitHub repository for the build script.

See Also

[london_collisions](#)

Examples

```
data(london_tree)
head(london_tree)
```

print.circular_scan *Print Method for circular_scan Objects*

Description

Print Method for circular_scan Objects

Usage

```
## S3 method for class 'circular_scan'  
print(x, max_show = 10L, ...)
```

Arguments

| | |
|----------|--|
| x | An object of class "circular_scan". |
| max_show | Integer. Maximum number of region IDs to display in full before truncating with "... and N more". The default of 10L keeps console output compact for large clusters; set max_show = -1L (or any value larger than the cluster size) to print every region. Mirrors the convention used by tibble for printing wide tables. |
| ... | Further arguments passed to or from other methods. |

Value

Invisibly returns x (the input object of class "circular_scan"), unchanged. Called for the side effect of printing a human-readable summary of the scan result to the console: the total cases and population, the number of regions scanned, the number of Monte Carlo simulations, and the contents of the most likely cluster (region IDs, cases, expected count, population, relative risk, log-likelihood ratio, and p-value).

print.sequential_scan *Print Method for sequential_scan Objects*

Description

Print Method for sequential_scan Objects

Usage

```
## S3 method for class 'sequential_scan'  
print(x, max_show = 10L, ...)
```

Arguments

| | |
|----------|--|
| x | An object of class "sequential_scan". |
| max_show | Integer. Maximum number of region IDs (or leaf IDs, for tree-only scans) to display in full per iteration before truncating with "... and N more". Default 10L; set max_show = -1L to print every value. |
| ... | Further arguments passed to or from other methods. |

Value

Invisibly returns x (the input object of class "sequential_scan"), unchanged. Called for the side effect of printing a human-readable summary of the sequential scan result to the console: the scan type, the buffer size, the number of iterations performed, the significance threshold, the number of significant clusters, and a per-iteration table of detected clusters.

| | |
|-----------------|---|
| print.tree_scan | <i>Print Method for tree_scan Objects</i> |
|-----------------|---|

Description

Print Method for tree_scan Objects

Usage

```
## S3 method for class 'tree_scan'
print(x, max_show = 10L, ...)
```

Arguments

| | |
|----------|--|
| x | An object of class "tree_scan". |
| max_show | Integer. Maximum number of leaf IDs to display in full before truncating with "... and N more". The default of 10L keeps console output compact when a node spans hundreds or thousands of leaves (such as the root of a deep tree); set max_show = -1L to print every leaf. |
| ... | Further arguments passed to or from other methods. |

Value

Invisibly returns x (the input object of class "tree_scan"), unchanged. Called for the side effect of printing a human-readable summary of the scan result to the console: the total cases and population, the number of tree nodes, the number of Monte Carlo simulations, the contents of the most likely cluster (node ID, leaf IDs, cases, expected count, log-likelihood ratio, and p-value), and the top significant cuts at the chosen significance threshold.

```
print.treespatial_scan
```

Print Method for treespatial_scan Objects

Description

Print Method for treespatial_scan Objects

Usage

```
## S3 method for class 'treespatial_scan'
print(x, max_show = 10L, ...)
```

Arguments

| | |
|----------|---|
| x | An object of class "treespatial_scan". |
| max_show | Integer. Maximum number of leaf IDs and region IDs to display in full before truncating with "... and N more". The default of 10L keeps console output compact when the most likely cluster spans many leaves (for example, when the root node maximises the likelihood ratio for an aggregated denominator) or many regions; set max_show = -1L to print every value. Mirrors the convention used by tibble . |
| ... | Further arguments passed to or from other methods. |

Value

Invisibly returns x (the input object of class "treespatial_scan"), unchanged. Called for the side effect of printing a human-readable summary of the scan result to the console: the total population, the number of regions and tree nodes, the number of Monte Carlo simulations, and the contents of the most likely cluster (tree node, leaf IDs, region IDs, cases, expected count, population, relative risk, log-likelihood ratio, and p-value).

```
rj_mortality
```

Rio de Janeiro Infant Mortality (2016)

Description

Combined long-format dataset of infant mortality in the 92 municipalities of Rio de Janeiro state, Brazil, 2016. Each row represents a (municipality, ICD-10 leaf) combination with at least one death; missing combinations are implicitly zero. Use together with [rj_tree](#).

Usage

```
rj_mortality
```

Format

A data.frame in long format with columns:

region_id Integer identifier of the municipality.

ibge_code 6-digit IBGE municipality code.

name Municipality name.

population IBGE municipal population estimate for 2016.

live_births Number of live births in 2016 (SINASC). Used as the population denominator in Section 5.2 of Cancado et al. (2025).

x Longitude of the municipality centroid.

y Latitude of the municipality centroid.

node_id Character ICD-10 leaf code (4 characters), matching a leaf of [rj_tree](#).

cases Integer count of infant deaths.

Details

To reproduce Section 5.2 of Cancado et al. (2025), use `live_births` as the population denominator:

```
data <- rj_mortality
data$population <- data$live_births
treespatial_scan(data, rj_tree, ...)
```

Municipality polygons can be obtained via `geobr::read_municipality()`.

Source

Population: IBGE municipal estimates. Live births: DATASUS/SINASC via TabNet. Deaths: DATASUS/SIM microdata via OpenDATASUS (<https://opendatasus.saude.gov.br>). Centroids: geobr.

References

Cancado, A.L.F., Oliveira, G.S., Quadros, A.V.C., Duczmal, L. (2025). A tree-spatial scan statistic. *Environmental and Ecological Statistics*, 32, 953–978. doi:10.1007/s1065102500670w

See Also

[rj_tree](#)

Examples

```
data(rj_mortality)
head(rj_mortality)
cat("Total deaths:", sum(rj_mortality$cases), "\n")
```

`rj_tree`*Rio de Janeiro Infant Mortality - ICD-10 Tree*

Description

ICD-10 hierarchy used by the `rj_mortality` dataset. Three levels: Chapter -> 3-character category -> 4-character subcategory.

Usage`rj_tree`**Format**

A data.frame with 622 rows and 2 columns:

node_id Character identifier of each ICD-10 node.

parent_id Character identifier of the parent node. NA for the root.

Details

The tree has 410 leaves (4-character ICD-10 codes) and 622 total nodes.

Source

Constructed from the leaf-level codes in `rj_mortality`, which in turn come from the Brazilian Mortality Information System (SIM) maintained by DATASUS. See `data-raw/` in the GitHub repository for the build script.

See Also

`rj_mortality`

Examples

```
data(rj_tree)
head(rj_tree)
```

sequential_scan *Sequential Scan for Secondary Clusters*

Description

Implements the sequential adjustment of Zhang, Assuncao and Kulldorff (2010) for detecting secondary clusters. After the most likely cluster (MLC) is detected and found significant, the regions composing it (optionally together with a buffer of nearest-neighbour regions) are *removed* from the dataset — treated as a "lake" with no population and no cases — and the scan is re-run on the reduced data with a fresh Monte Carlo simulation. The procedure is iterated until the MLC of the current reduced data is no longer significant, or `max_iter` is reached.

Usage

```
sequential_scan(
  cases = NULL,
  population = NULL,
  region_id = NULL,
  x = NULL,
  y = NULL,
  node_id = NULL,
  tree = NULL,
  tree_node_id = NULL,
  tree_parent_id = NULL,
  max_iter = 5L,
  alpha = 0.05,
  nsim = 999L,
  max_pop_pct = 0.5,
  buffer_size = 0L,
  model = c("poisson", "binomial"),
  seed = NULL,
  verbose = TRUE,
  n_cores = 1L
)
```

Arguments

| | |
|---|--|
| <code>cases</code> | Numeric vector. For tree-spatial scan: one entry per (region, leaf) row. For circular: one entry per region. For tree-only: one entry per leaf. |
| <code>population</code> | Numeric vector parallel to <code>cases</code> . |
| <code>region_id, x, y</code> | Vectors parallel to <code>cases</code> (omit for tree-only scan). |
| <code>node_id</code> | Vector parallel to <code>cases</code> (omit for circular and tree-only scans). |
| <code>tree</code> | Tree as a 2-column data.frame (<code>node_id</code> , <code>parent_id</code>), or use <code>tree_node_id/tree_parent_id</code> . Omit for circular scan. |
| <code>tree_node_id, tree_parent_id</code> | Optional. Parallel vectors as an alternative to <code>tree</code> . |

| | |
|-------------|--|
| max_iter | Integer. Maximum number of iterations (including the primary MLC). Default 5. |
| alpha | Numeric. Significance level. Iteration stops when the MLC p-value of the current reduced data exceeds alpha. Default 0.05. |
| nsim | Integer. Monte Carlo replications per iteration. Default 999. |
| max_pop_pct | Numeric. Maximum zone-size constraint, passed to the inner scans. Default 0.5. |
| buffer_size | Integer. Number of nearest-neighbour regions to remove together with each detected cluster, computed by Euclidean distance from each cluster region to the remaining ones. Default 0. Zhang et al. (2010) report that the type I error and power are essentially insensitive to the buffer size and that buffer_size = 0 is generally adequate. Ignored for tree-only scans. |
| model | Character. "poisson" (default) or "binomial". |
| seed | Integer or NULL. Seed for the first iteration; subsequent iterations advance the RNG state. |
| verbose | Logical. Print progress at each iteration. |
| n_cores | Integer. OpenMP threads passed to inner scans. |

Details

This differs from [filter_clusters](#), which scans the single-pass candidate pool for non-overlapping clusters (the original Cancado et al. 2025 criterion). The sequential approach computes a fresh, un-conservative p-value for each secondary cluster, conditional on the prior detections.

Dispatch on the supplied arguments selects one of three scan types:

- tree-spatial: all of cases, population, region_id, x, y, node_id, tree are required;
- circular: cases, population, region_id, x, y (no node_id / tree);
- tree-only: cases, population, tree (no spatial inputs). buffer_size is ignored for the tree-only case.

Value

An object of class "sequential_scan" with components:

clusters A data.frame with one row per iteration performed, with columns iteration, node_id (only for tree-spatial / tree-only scans), n_regions (only for scans with a spatial component), cases, expected, population, rr (only for scans with a spatial component), llr, pvalue, and a logical significant flag (pvalue <= alpha). The list- columns region_ids and/or leaf_ids carry the cluster composition.

iterations A list with the full scan result of each iteration.

regions, tree, alpha, nsim, buffer_size, n_iter, scan_type Bookkeeping fields. n_iter is the number of iterations actually performed.

References

- Zhang, Z., Assuncao, R., & Kulldorff, M. (2010). Spatial scan statistics adjusted for multiple clusters. *Journal of Probability and Statistics*, 2010, 642379.
- Cancado, A. L. F., Oliveira, G. S., Quadros, A. V. C., & Duczmal, L. H. (2025). A tree-spatial scan statistic. *Environmental and Ecological Statistics*, 32, 953-978. doi:10.1007/s1065102500670w
- Kulldorff, M. (1997). A spatial scan statistic. *Communications in Statistics - Theory and Methods*, 26(6), 1481-1496.

See Also

[treespatial_scan](#), [circular_scan](#), [tree_scan](#), [filter_clusters](#), [get_cluster_regions](#)

Examples

```
data(london_collisions); data(london_tree)
result <- sequential_scan(
  cases      = london_collisions$cases,
  population = london_collisions$population,
  region_id  = london_collisions$region_id,
  x          = london_collisions$x,
  y          = london_collisions$y,
  node_id    = london_collisions$node_id,
  tree       = london_tree,
  max_iter = 3, nsim = 99, seed = 42
)
print(result)
```

summary.circular_scan *Summary Method for circular_scan Objects*

Description

Prints the same fields as `print.circular_scan()`, followed by a numeric summary of the simulated log-likelihood-ratio distribution under the null. Useful for checking that the Monte Carlo replicates produced a reasonable spread relative to the observed test statistic.

Usage

```
## S3 method for class 'circular_scan'
summary(object, ...)
```

Arguments

`object` An object of class "circular_scan".

`...` Further arguments passed to `print.circular_scan()`. In particular, `max_show` controls how many region IDs of the most-likely cluster are printed in full before truncating with "... and N more"; see [print.circular_scan](#) for details.

Value

Invisibly returns object (the input object of class "circular_scan"), unchanged. Called for the side effect of printing the same fields as `print.circular_scan()`, followed by a numeric summary (min, quartiles, median, mean, max) of the simulated log-likelihood-ratio distribution under the null.

```
summary.sequential_scan
```

Summary Method for sequential_scan Objects

Description

Summary Method for sequential_scan Objects

Usage

```
## S3 method for class 'sequential_scan'
summary(object, ...)
```

Arguments

object An object of class "sequential_scan".
 ... Passed to `print.sequential_scan()`.

Value

Invisibly returns object. Called for the side effect of printing the same fields as `print.sequential_scan()` followed by, for each iteration, the cluster composition (region IDs or leaf IDs).

```
summary.tree_scan
```

Summary Method for tree_scan Objects

Description

Prints the same fields as `print.tree_scan()`, followed by the full table of all candidate cuts (not just significant ones) ordered by decreasing log-likelihood ratio.

Usage

```
## S3 method for class 'tree_scan'
summary(object, ...)
```

Arguments

object An object of class "tree_scan".
 ... Further arguments passed to `print.tree_scan()`. In particular, `max_show` controls how many leaf IDs of the most-likely cluster are printed in full before truncating with "... and N more"; see [print.tree_scan](#) for details.

Value

Invisibly returns object (the input object of class "tree_scan"), unchanged. Called for the side effect of printing the same fields as `print.tree_scan()`, followed by the full table of all candidate cuts (not just significant ones) ordered by decreasing log-likelihood ratio.

`summary.treespatial_scan`*Summary Method for treespatial_scan Objects*

Description

Prints the same fields as `print.treespatial_scan()`, followed by the top-10 branches by total case count and a numeric summary of the simulated log-likelihood-ratio distribution under the null. Useful for diagnosing how heavily one branch of the tree dominates the dataset and whether the observed maximum LR is a clear outlier against the simulated null.

Usage

```
## S3 method for class 'treespatial_scan'  
summary(object, ...)
```

Arguments

| | |
|---------------------|--|
| <code>object</code> | An object of class "treespatial_scan". |
| <code>...</code> | Further arguments passed to <code>print.treespatial_scan()</code> . In particular, <code>max_show</code> controls how many leaf IDs and region IDs of the most-likely cluster are printed in full before truncating with "... and N more"; see print.treespatial_scan for details. |

Value

Invisibly returns object (the input object of class "treespatial_scan"), unchanged. Called for the side effect of printing the same fields as `print.treespatial_scan()`, followed by the top-10 branches by total case count and a numeric summary (min, quartiles, median, mean, max) of the simulated log-likelihood-ratio distribution under the null.

| | |
|-----------|----------------------------------|
| tree_scan | <i>Tree-Based Scan Statistic</i> |
|-----------|----------------------------------|

Description

Performs the tree-based scan statistic for detecting clusters in hierarchical data. Uses a Poisson or binomial model with Monte Carlo simulation (implemented in C++ via Rcpp) for significance testing.

Usage

```
tree_scan(
  tree = NULL,
  cases,
  population = NULL,
  nsim = 999L,
  alpha = 0.05,
  model = c("poisson", "binomial"),
  seed = NULL,
  n_cores = 1L,
  tree_node_id = NULL,
  tree_parent_id = NULL
)
```

Arguments

| | |
|------------------------------|--|
| tree | A data.frame with columns node_id and parent_id. Root node(s) must have parent_id = NA. Alternatively, pass the tree as parallel vectors via tree_node_id and tree_parent_id. |
| cases | A numeric vector of case counts at the leaf level. |
| population | A numeric vector of population at the leaf level, or a single value. For the binomial model, population is the number of trials (cases + controls) per leaf and is required. For the Poisson model, defaults to 1 per leaf if NULL. |
| nsim | Integer. Number of Monte Carlo simulations. Default is 999. |
| alpha | Numeric. Significance level. Default is 0.05. |
| model | Character. Likelihood model: either "poisson" (default) or "binomial". |
| seed | Integer or NULL. Random seed for the Monte Carlo loop. When non-NULL, the user's pre-existing RNG state is saved on entry and restored on exit, so the seed argument affects only this call and does not leak into subsequent draws in the user's session. |
| n_cores | Integer. Number of OpenMP threads for the Monte Carlo loop. Default is 1L (serial). Set higher to parallelize. |
| tree_node_id, tree_parent_id | Optional parallel vectors describing the tree as an alternative to the tree data.frame. Both must have the same length, and the root node(s) must have tree_parent_id = NA. Ignored when tree is supplied. |

Value

An object of class "tree_scan" (see package help for details).

References

Kulldorff, M., Fang, Z., & Walsh, S. J. (2003). A tree-based scan statistic for database disease surveillance. *Biometrics*, 59(2), 323–331.

See Also

[circular_scan](#), [treespatial_scan](#), [aggregate_tree](#)

Examples

```
tree <- data.frame(
  node_id = c(1, 2, 3, 4, 5, 6, 7, 8),
  parent_id = c(NA, 1, 1, 2, 2, 3, 3, 3)
)
cases <- c(50, 5, 3, 2, 4)
pop <- c(100, 100, 100, 100, 100)

result <- tree_scan(tree, cases, population = pop, nsim = 99)
print(result)
```

| | |
|------------------|------------------------------------|
| treespatial_scan | <i>Tree-Spatial Scan Statistic</i> |
|------------------|------------------------------------|

Description

Performs the tree-spatial scan statistic, combining Kulldorff's circular scan (spatial clusters) with the tree-based scan (hierarchical data mining). Searches all combinations of spatial zones and tree branches to identify pairs (z, g) with significantly more cases than expected.

Usage

```
treespatial_scan(
  cases,
  population,
  region_id,
  x,
  y,
  node_id,
  tree = NULL,
  tree_node_id = NULL,
  tree_parent_id = NULL,
  max_pop_pct = 0.5,
  nsim = 999L,
  alpha = 0.05,
```

```

  model = c("poisson", "binomial"),
  seed = NULL,
  n_cores = 1L
)

```

Arguments

| | |
|------------------------------|---|
| cases | Numeric vector. Number of cases observed for each (region, leaf) pair. Length n . |
| population | Numeric vector. Population (or denominator) of the region for each row. The same value should be repeated across all rows of a given region; if it varies, the first occurrence per region is used and a warning is issued. |
| region_id | Vector of region identifiers. Length n . |
| x, y | Numeric vectors of region centroid coordinates. Like <code>population</code> , these should be constant within region. |
| node_id | Vector of tree leaf identifiers. Length n . Each value must match a leaf of the tree. |
| tree | A <code>data.frame</code> with columns <code>node_id</code> and <code>parent_id</code> . The root node(s) must have <code>parent_id = NA</code> . As an alternative, pass <code>tree_node_id</code> and <code>tree_parent_id</code> as parallel vectors instead of this argument. |
| tree_node_id, tree_parent_id | Optional. Parallel vectors describing the tree edges, used as an alternative to <code>tree</code> . If both <code>tree</code> and these vectors are supplied, an error is raised. |
| max_pop_pct | Numeric. Maximum proportion of total population allowed inside a zone. Default 0.5. |
| nsim | Integer. Number of Monte Carlo simulations. Default 999. |
| alpha | Numeric. Significance level. Default 0.05. |
| model | Character. "poisson" (default) or "binomial". |
| seed | Integer or NULL. Random seed for the Monte Carlo loop. When non-NULL, the user's pre-existing RNG state is saved on entry and restored on exit, so the seed argument affects only this call and does not leak into subsequent draws in the user's session. |
| n_cores | Integer. OpenMP threads for the Monte Carlo loop. Default 1L (serial). |

Details

Inputs are passed as parallel vectors of equal length (one entry per (region, tree-leaf) observation). The user is responsible for choosing which column to use as `population` (e.g., total population, live births, person-years), making the choice of denominator explicit.

Secondary clusters. The returned object contains the most likely cluster as well as the full set of evaluated (zone, branch) pairs in `secondary_clusters`. To obtain the distinct secondary clusters as described in Section 5.1.1 of Cancado et al. (2025) (filtering out pairs that overlap in regions or branches with already-retained clusters), use `filter_clusters` or `get_cluster_regions` with `n_clusters > 1`.

Value

An object of class "treespatial_scan".

References

Cancado, A. L. F., Oliveira, G. S., Quadros, A. V. C., & Duczmal, L. (2025). A tree-spatial scan statistic. *Environmental and Ecological Statistics*, 32, 953–978. doi:10.1007/s1065102500670w

See Also

[circular_scan](#), [tree_scan](#), [aggregate_tree](#), [filter_clusters](#), [get_cluster_regions](#), [sequential_scan](#)

Examples

```
set.seed(123)
n_regions <- 10
tree <- data.frame(
  node_id = c(1, 2, 3, 4, 5, 6, 7),
  parent_id = c(NA, 1, 1, 2, 2, 3, 3)
)
# Build vectors: one row per (region, leaf) combination
grid <- expand.grid(region_id = 1:n_regions, node_id = c(4, 5, 6, 7))
xs <- runif(n_regions, 0, 10)[grid$region_id]
ys <- runif(n_regions, 0, 10)[grid$region_id]
cs <- rpois(nrow(grid), lambda = 5)
cs[grid$node_id == 4 & grid$region_id %in% 1:3] <- rpois(3, 30)

result <- treespatial_scan(
  cases = cs,
  population = rep(1000, nrow(grid)),
  region_id = grid$region_id,
  x = xs,
  y = ys,
  node_id = grid$node_id,
  tree = tree,
  nsim = 99
)
print(result)
```

Index

* datasets

- chicago_crimes, [6](#)
 - chicago_map, [8](#)
 - chicago_tree, [8](#)
 - fl_deaths, [12](#)
 - london_boroughs_map, [16](#)
 - london_collisions, [17](#)
 - london_tree, [18](#)
 - rj_mortality, [21](#)
 - rj_tree, [23](#)
- aggregate_tree, [3](#), [4](#), [30](#), [32](#)
- build_zones, [3](#), [5](#)
- chicago_crimes, [6](#), [8](#), [9](#)
- chicago_map, [7](#), [8](#)
- chicago_tree, [6](#), [7](#), [8](#)
- circular_scan, [3](#), [9](#), [11](#), [15](#), [26](#), [30](#), [32](#)
- filter_clusters, [3](#), [10](#), [11](#), [14](#), [15](#), [25](#), [26](#),
[31](#), [32](#)
- fl_deaths, [12](#)
- generate_example_data, [13](#)
- get_cluster_regions, [3](#), [10](#), [14](#), [16](#), [26](#), [31](#),
[32](#)
- london_boroughs_map, [16](#), [17](#)
- london_collisions, [16](#), [17](#), [18](#)
- london_tree, [17](#), [18](#)
- print.circular_scan, [19](#), [26](#)
- print.sequential_scan, [19](#)
- print.tree_scan, [20](#), [27](#)
- print.treespatial_scan, [21](#), [28](#)
- rj_mortality, [21](#), [23](#)
- rj_tree, [21](#), [22](#), [23](#)
- sequential_scan, [3](#), [10](#), [11](#), [15](#), [24](#), [32](#)
- summary.circular_scan, [26](#)
- summary.sequential_scan, [27](#)
- summary.tree_scan, [27](#)
- summary.treespatial_scan, [28](#)
- tree_scan, [3](#), [10](#), [11](#), [26](#), [29](#), [32](#)
- treespatial_scan, [3](#), [10](#), [11](#), [13](#), [15](#), [26](#), [30](#),
[30](#)
- treeSS (treeSS-package), [3](#)
- treeSS-package, [3](#)