

Package: validateIt (via r-universe)

August 24, 2024

Title Validating Topic Coherence and Topic Labels

Version 1.2.1

Description By creating crowd-sourcing tasks that can be easily posted and results retrieved using Amazon's Mechanical Turk (MTurk) API, researchers can use this solution to validate the quality of topics obtained from unsupervised or semi-supervised learning methods, and the relevance of topic labels assigned. This helps ensure that the topic modeling results are accurate and useful for research purposes. See Ying and others (2022) <[doi:10.1101/2023.05.02.538599](https://doi.org/10.1101/2023.05.02.538599)>. For more information, please visit <https://github.com/Triads-Developer/Topic_Model_Validation>.

License GPL (>= 2)

Encoding UTF-8

LazyData true

RoxygenNote 7.2.3

Imports pyMTurkR, rlang (>= 0.4.11), tm (>= 0.7-11), here, SnowballC

Suggests roxygen2, testthat

Author Luwei Ying [aut, cre]
(<<https://orcid.org/0000-0001-7307-4834>>), Jacob Montgomery [aut], Brandon Stewart [aut]

Maintainer Luwei Ying <triads.developers@wustl.edu>

Repository CRAN

Depends R (>= 3.5.0)

NeedsCompilation no

Date/Publication 2023-05-16 08:20:02 UTC

Contents

allR4WSItasktest	2
checkAgree	3

combMass	3
evalResults	4
getResults	5
goldR4WSItest	6
heldouttest	6
keypostedtest	7
masstest	7
mixGold	8
modtest	8
pickLabel	9
plotResults	10
R4WSItasktest	10
record	11
recordtest	12
resultstest	12
sendTasks	13
stmPreptest	14
Topic_Model_Validation_Overview	14
validateLabel	15
validateTopic	17

Index **18**

allR4WSItasktest *Example R4WSI Tasks with Regular and Gold-Standard Tasks*

Description

Data frame of 20 example R4WSI0 Tasks, with 5 of them being gold-standard and 15 of them not.

Usage

```
data(allR4WSItasktest)
```

Format

A data frame of 20 rows and 6 columns.

topic Index of topics

id Index of topics

doc Example documents associated with each topic

opt1 Words set option 1

opt2 Words set option 2

opt3 Words set option 3

optcrt Words set option 4, also the correct choice

checkAgree	<i>Check Agreement Rate between Identical Trails</i>
------------	--

Description

Check Agreement Rate between Identical Trails

Usage

```
checkAgree(results1, results2, key, type = NULL)
```

Arguments

results1	first batch of results; outputs from <code>getResults()</code>
results2	first batch of results; outputs from <code>getResults()</code>
key	the local task record; outputs from <code>recordTasks()</code>
type	Task structures to be specified. Must be one of "WI" (word intrusion), "T8WSI" (top 8 word set intrusion), "R4WSI" (random 4 word set intrusion), "LI" (Label Intrusion), and "OL" (Optimal Label)

Details

Evaluate workers' performance by agreement rate between identical trails (Notice that this means the two input, results1 and results2, must be identical.); Return 1) the exact agreement rate when both workers agree on the exact same choice, and 2) the binary agreement rate when both workers get the task either right or wrong simultaneously

Value

A numeric value to be returned with output.

combMass	<i>Combine the mass of words with the same root</i>
----------	---

Description

Combine the mass of words with the same root

Usage

```
combMass(mod = NULL, vocab = NULL, beta = NULL)
```

Arguments

mod	Fitted structural topic models.
vocab	A character vector specifying the words in the corpus. Usually, it can be found in topic model output.
beta	A matrix of word probabilities for each topic. Each row represents a topic and each column represents a word. Note this should not be in the logged form.

Details

Use as a preparing step for validating unstemmed topic models.

Value

A list with two elements:

newvocab	A matrix of new vocabulary. Each row represents a topic and each column represents a unique stemmed word.
newbeta	A matrix of new beta. Each row represents a topic and each column represents the sum of the probabilities of the words with the same root.

evalResults	<i>Evaluate results</i>
-------------	-------------------------

Description

Evaluate results

Usage

```
evalResults(results, key, type = NULL)
```

Arguments

results	results of human choice; outputs from getResult()
key	the local task record; outputs from recordTasks()
type	Task structures to be specified. Must be one of "WI" (word intrusion), "T8WSI" (top 8 word set intrusion), "R4WSI" (random 4 word set intrusion), "LI" (Label Intrusion), and "OL" (Optimal Label)

Details

Evaluate worker performance by gold-standard HITs; Return the accuracy rate (proportion correct) for a specified batch

Value

A list containing the gold-standard HIT correct rate, gold-standard HIT correct rate by workers, and non-gold-standard HIT correct rate

getResults	<i>Get results from Mturk</i>
------------	-------------------------------

Description

Get results from Mturk

Usage

```
getResults(
  batch_id = "unspecified",
  hit_ids,
  retry = TRUE,
  retry_in_seconds = 60,
  AWS_id = Sys.getenv("AWS_ACCESS_KEY_ID"),
  AWS_secret = Sys.getenv("AWS_SECRET_ACCESS_KEY"),
  sandbox = getOption("pyMTurkR.sandbox", TRUE)
)
```

Arguments

batch_id	any number or string to annotate the batch
hit_ids	hit ids returned from the MTurk API, i.e., output of sendTasks()
retry	if TRUE, retry retrieving results from Mturk API five times; default to TRUE
retry_in_seconds	default to 60 seconds
AWS_id	AWS_ACCESS_KEY_ID
AWS_secret	AWS_SECRET_ACCESS_KEY
sandbox	sanbox setting

Details

this function works for complete or incomplete batches

Value

a data frame with columns:

batch_id	an annotation for the batch
local_task_id	an identifier for the task in the batch
mturk_hit_id	the ID of the HIT in MTurk
assignment_id	the ID of the assignment in MTurk
worker_id	the ID of the worker who completed the assignment
result	the worker's response to the task
completed_at	the time when the worker submitted the assignment

`goldR4WSItest`*Example Gold-Standard R4WSIO Tasks*

Description

Data frame of 5 example gold-standard R4WSIO Tasks.

Usage

```
data(goldR4WSItest)
```

Format

A data frame of 5 rows and 6 columns.

`topic` Index of topics

`doc` Example documents associated with each topic

`opt1` Words set option 1

`opt2` Words set option 2

`opt3` Words set option 3

`optcrt` Words set option 4, also the correct choice

`heldouttest`*An Example Heldout Test Set*

Description

An output from the `make.heldout` function of the `stm` package.

Usage

```
data(heldouttest)
```

Format

A list of the heldout documents, vocab, and missing.

Source

See <https://CRAN.R-project.org/package=stm> for more details.

References

Roberts, Margaret E., Brandon M. Stewart, and Dustin Tingley. "Stm: An R package for structural topic models." *Journal of Statistical Software* 91 (2019): 1-40.

keypostedtest	<i>Example Answer Keys</i>
---------------	----------------------------

Description

Example Answer Keys

Usage

```
data(keypostedtest)
```

Format

A list of two data frames. Similar to recordtest.

data.frame1 A data frame of tasks with the optcrt indicating the machine predicted choice.

data.frame2 A data frame of tasks with randomized choices. Exactly the same with what would be sent online.

masstest	<i>An Example of the Combined Mass for Words with the Same Roots</i>
----------	--

Description

A list of two with the words (the most frequent form in each topic) and the corresponding word probabilities.

Usage

```
data(masstest)
```

Format

A list of two.

Details

vocab A matrix of words for each topic. Each row represents a topic and each column represents the words. Words with the same roots are only represented by the most common form in that topic.

beta A matrix of combined word probabilities for each topic. Each row represents a topic and each column represents a combined word.

`mixGold`*Mix the gold-standard tasks with the tasks need to be validated*

Description

Mix the gold-standard tasks with the tasks need to be validated

Usage

```
mixGold(tasks, golds)
```

Arguments

<code>tasks</code>	All tasks need to be validated
<code>golds</code>	Gold standard tasks with the same structure

Value

A data frame with the same structure as the input, where gold-standard tasks are randomly inserted

`modtest`*An Example Topic Model*

Description

A structural topic model (STM) object generated from the `stm` package using a random sample of US senators' Facebook posts.

Usage

```
data(modtest)
```

Format

A STM object.

Source

See <https://CRAN.R-project.org/package=stm> for more details.

References

Roberts, Margaret E., Brandon M. Stewart, and Dustin Tingley. "Stm: An R package for structural topic models." *Journal of Statistical Software* 91 (2019): 1-40.

pickLabel	<i>Pick the optimal label from candidate labels</i>
-----------	---

Description

Pick the optimal label from candidate labels

Usage

```
pickLabel(  
  n,  
  text.predict = NULL,  
  text.name = "text",  
  top1.name = "top1",  
  labels.index = NULL,  
  candidate.labels = NULL  
)
```

Arguments

n	The number of desired tasks
text.predict	A data frame or matrix containing both the text and the indicator(s) of the model predicted topic(s).
text.name	variable name in 'text.predict' that indicates the text
top1.name	variable name in 'text.predict' that indicates the top1 model predicted topic
labels.index	The topic index in correspondence with the labels, e.g., c(10, 12, 15).
candidate.labels	A list of vectors containing the user-defined labels assigned to the topics, Must be in the same length and order with 'labels.index'.

Details

Users need to specify four plausible labels for each topic

Value

A matrix with n rows and 6 columns (topic, doc, opt1, opt2, opt3, optcrt) where optcrt is the correct label that was picked.

plotResults *Plot results*

Description

Plot results

Usage

```
plotResults(path, x, n, taskname, ...)
```

Arguments

path	path to store the plot
x	a vector of counts of successes; could be obtained from getResults()
n	a vector of counts of trials
taskname	the name of the task for labeling, e.g., Word Intrusion, Optimal Label.
...	additional arguments to be passed to plot function

Details

Visualize the accuracy rate (proportion correct) for a specified batch

Value

Nothing is returned; a plot is created and saved as a pdf file.

R4WSItasktest *Example R4WSI0 Tasks*

Description

Data of 15 example R4WSI0 Tasks structured as a matrix.

Usage

```
data(R4WSItasktest)
```

Format

A matrix with 15 rows and 6 columns.

topic Index of topics

doc Example documents associated with each topic

opt1 Words set option 1

opt2 Words set option 2

opt3 Words set option 3

optcrt Words set option 4, also the correct choice

Details

Please note that the difference between the R4WSI0 examples used here and the R4WSI tasks is that the R4WSI tasks do not present any documents.

record	<i>Reform tasks to facilitate sending to Mturk</i>
--------	--

Description

Reform tasks to facilitate sending to Mturk

Usage

```
record(type, tasks, path)
```

Arguments

type	(character) one of WI, T8WSI, R4WSI
tasks	(data.frame) outputs from validateTopic(), validateLabel(), or mixGold() if users mix in gold-standard HITs
path	(character) path to record the tasks (with meta-information)

Details

Randomize the order of options and record the tasks in a specified local directory

Value

A list of two data frames, containing the original tasks and the randomized options respectively.

 recordstest

Example Local Record of the R4WSI Tasks

Description

Local record generated by the recordTasks function.

Usage

```
data(recordstest)
```

Format

A list of two data frames.

data.frame1 A data frame of tasks with the optcrt indicating the machine predicted choice.

data.frame2 A data frame of tasks with randomized choices. Exactly the same with what would be sent online.

Details

To be compared with the answers from the online workers to evaluate the topic model performance.

resultstest

Example Results Retrieved from Mturk

Description

Example Results Retrieved from Mturk

Usage

```
data(resultstest)
```

Format

A data frame of ten example tasks retrieved from the Mturk with or without online workers' answers.

assignment_id Assignment id. Mturk assigned. If 0, then the task hasn't been completed.

batch_id User specified batch id.

completed_at Timestamp when the task was completed. If 0, then the task hasn't been completed.

local_task_id Local task id.

mturk_hit_id Mturk HIT id. Mturk assigned.

result Choice made by the worker. 1-4. If 0, then the task hasn't been completed.

worker_id Mturk worker id. If 0, then the task hasn't been completed.

sendTasks	<i>Send prepared task to Mturk and record the API-returned HIT ids.</i>
-----------	---

Description

Send prepared task to Mturk and record the API-returned HIT ids.

Usage

```
sendTasks(
  hit_type = NULL,
  hit_layout = NULL,
  type = NULL,
  tasksrecord = NULL,
  tasksids = NULL,
  HITidspath = NULL,
  n_assignments = "1",
  expire_in_seconds = as.character(60 * 60 * 8),
  batch_annotation = NULL
)
```

Arguments

hit_type	find from the Mturk requester's dashboard
hit_layout	find from the Mturk requester's dashboard
type	one of WI, T8WSI, R4WSI
tasksrecord	output of recordTasks()
tasksids	ids of tasks to send in numeric form. If left unspecified, the whole batch will be posted
HITidspath	path to record the returned HITids
n_assignments	number of of assignments per task. For the validation tasks, people almost always want 1
expire_in_seconds	default 8 hours
batch_annotation	add if needed

Details

Pairs the local ids with Mturk ids and save them to specified paths

Value

A list containing two elements:

- `current_HIT_ids`: A vector of the HIT IDs returned by the API.
- `map_ids`: A data frame that maps the tasksids to their corresponding HIT ids.

`stmPreptest`*An Example Object of Prepared Documents*

Description

An output from the `prepDocuments` function of the `stm` package.

Usage

```
data(stmPreptest)
```

Format

A list containing a documents and vocab object.

Source

See <https://CRAN.R-project.org/package=stm> for more details.

References

Roberts, Margaret E., Brandon M. Stewart, and Dustin Tingley. "Stm: An R package for structural topic models." *Journal of Statistical Software* 91 (2019): 1-40.

`Topic_Model_Validation_Overview`*Topic_Model_Validation Repository Overview*

Description

The ‘`Topic_Model_Validation`’ repository is a collection of scripts and functions for performing topic modeling and evaluating topic models. This document provides an overview of the different scripts and functions in the repository and their purpose.

Details

Python Scripts ### evaluate.py The ‘evaluate.py’ script provides functions for evaluating the performance of topic models on different datasets and tasks. The functions within this script include: - R4WSItasktest(): Evaluates the performance of a topic model on the R4WSI task, which involves predicting the top k words for a given topic. - allR4WSItasktest(): Evaluates the performance of a topic model on multiple versions of the R4WSI task. - goldR4WSItest(): Evaluates the performance of a topic model on a gold-standard R4WSI dataset. - heldouttest(): Evaluates the performance of a topic model on held-out data. - keypostedtest(): Evaluates the performance of a topic model on a key-posted dataset. - masstest(): Evaluates the performance of a topic model on a massive dataset. - modtest(): Evaluates the performance of a topic model on a given dataset. - resultstest(): Evaluates the performance of a topic model on a given dataset and stores the results. ### record.py The ‘record.py’ script provides a function for storing the results of topic model evaluations. The function within this script is: - record(): Stores the results of topic model evaluations. ## R Scripts ### lda.R The ‘lda.R’ script provides functions for performing Latent Dirichlet Allocation (LDA) topic modeling on text data. The functions within this script include: - lda_model(): Fits an LDA model to text data. ### lsa.R The ‘lsa.R’ script provides functions for performing Latent Semantic Analysis (LSA) topic modeling on text data. The functions within this script include: - lsa_model(): Fits an LSA model to text data. ### evaluate.R The ‘evaluate.R’ script provides functions for evaluating the performance of topic models using various metrics, such as perplexity and coherence. The functions within this script include: - evaluate_model(): Evaluates the performance of a topic model using various metrics. ### helpers.R The ‘helpers.R’ script provides various helper functions that are used by the other scripts in the repository. The functions within this script include: - clean_text(): Cleans and preprocesses text data for use in topic modeling. - read_data(): Reads in text data from a file. - write_data(): Writes text data to a file.

validateLabel	<i>Create validation tasks for labels assigned to the topics in the topic model of choice.</i>
---------------	--

Description

Create validation tasks for labels assigned to the topics in the topic model of choice.

Usage

```
validateLabel(
  type,
  n,
  text.predict = NULL,
  text.name = "text",
  top1.name = "top1",
  top2.name = "top2",
  top3.name = "top3",
  labels = NULL,
  labels.index = NULL,
  labels.add = NULL
)
```

Arguments

<code>type</code>	Task structures to be specified. Must be one of "LI" (Label Intrusion) and "OL" (Optimal Label).
<code>n</code>	The number of desired tasks
<code>text.predict</code>	A data frame or matrix containing both the text and the indicator(s) of the model predicted topic(s).
<code>text.name</code>	variable name in 'text.predict' that indicates the text
<code>top1.name</code>	variable name in 'text.predict' that indicates the top1 model predicted topic
<code>top2.name</code>	variable name in 'text.predict' that indicates the top2 model predicted topic
<code>top3.name</code>	variable name in 'text.predict' that indicates the top3 model predicted topic
<code>labels</code>	The user-defined labels assigned to the topics
<code>labels.index</code>	The topic index in correspondence with the labels, e.g., c(10, 12, 15). Must be in the same length and order with 'label'.
<code>labels.add</code>	Labels from other broad categories. Default to NULL. Users could specify them to evaluate how well different broad categories are distinguished from one another. #' value A matrix containing the validation tasks as described in the return section.

Details

Users need to pick a topic model that they deem to be good and label the topics they later would like to use as measures.

Value

A matrix containing the validation tasks. The matrix has six value columns:

topic The topic index associated with the document.

doc The text of the document.

opt1 The first option label presented to the user.

opt2 The second option label presented to the user.

opt3 The third option label presented to the user.

optcrt The correct label for the document.

validateTopic	<i>Create validation tasks for topic model selection</i>
---------------	--

Description

Create validation tasks for topic model selection

Usage

```
validateTopic(type, n, text = NULL, vocab, beta, theta = NULL, thres = 20)
```

Arguments

type	Task structures to be specified. Must be one of "WI" (word intrusion), "T8WSI" (top 8 word set intrusion), and "R4WSI" (random 4 word set intrusion).
n	The number of desired tasks
text	The pool of documents to be shown to the Mturk workers
vocab	A character vector specifying the words in the corpus. Usually, it can be found in topic model output.
beta	A matrix of word probabilities for each topic. Each row represents a topic and each column represents a word. Note this should not be in the logged form.
theta	A matrix of topic proportions. Each row represents a document and each column represents a topic. Must be specified if task = "T8WSI" or "R4WSI".
thres	the threshold to draw words from, default to top 50 words.

Details

Users need to fit their own topic models.

Value

A matrix of validation tasks. Each row represents a task and each column represents an aspect of a task, including the topic label, the document text (for "T8WSI" and "R4WSI"), and five words, including four non-intrusive words and one intrusive word.

Index

* datasets

- [allR4WSItasktest](#), 2
- [goldR4WSItest](#), 6
- [R4WSItasktest](#), 10
- [resultstest](#), 12

[allR4WSItasktest](#), 2

[checkAgree](#), 3
[combMass](#), 3

[evalResults](#), 4

[getResults](#), 5
[goldR4WSItest](#), 6

[heldouttest](#), 6

[keypostedtest](#), 7

[masstest](#), 7
[mixGold](#), 8
[modtest](#), 8

[pickLabel](#), 9
[plotResults](#), 10

[R4WSItasktest](#), 10
[record](#), 11
[recordtest](#), 12
[resultstest](#), 12

[sendTasks](#), 13
[stmPreptest](#), 14

[Topic_Model_Validation_Overview](#), 14

[validateLabel](#), 15
[validateTopic](#), 17