Package: wdnet (via r-universe)

October 9, 2026

Title Weighted and Directed Networks

Version 1.2.4

Date 2026-03-09

Maintainer Yelie Yuan <yelie.yuan@gmail.com>

Description Assortativity coefficients, centrality measures, and clustering coefficients for weighted and directed networks. Rewiring unweighted networks with given assortativity coefficients. Generating general preferential attachment networks.

Depends R (>= 4.4.0)

License GPL (>= 3.0)

Encoding UTF-8

Imports CVXR (>= 1.8.1), igraph (>= 2.2.2), Matrix (>= 1.7.4), rARPACK (>= 0.11-0), RcppXPtrUtils (>= 0.1.3), stats, wdm (>= 0.2.6)

LinkingTo Rcpp, RcppArmadillo

BugReports https://gitlab.com/wdnetwork/wdnet/-/issues

URL https://gitlab.com/wdnetwork/wdnet

RoxygenNote 7.3.3

Suggests testthat (>= 3.0.0)

NeedsCompilation yes

Author Yelie Yuan [aut, cre], Tiandong Wang [aut], Jun Yan [aut], Panpan Zhang [aut]

Repository https://cran.r-universe.dev

Date/Publication 2026-03-10 09:40:02 UTC

RemoteUrl https://github.com/cran/wdnet

RemoteRef HEAD

RemoteSha 782212815dca7c7b6948913b9c320047e1eea461

Contents

+.rpacontrol . . . 2
adj_to_wdnet . . . 3
assortcoef . . . 4
centrality . . . 5
clustcoef . . . 7
cvxr_control . . . 9
dprewire . . . 10
dprewire.range . . . 12
edgelist_to_wdnet . . . 13
igraph_to_wdnet . . . 14
is_wdnet . . . 15
plot.wdnet . . . 15
print.rpacontrol . . . 16
print.wdnet . . . 16
rpa_control_edgeweight . . . 17
rpa_control_newedge . . . 18
rpa_control_preference . . . 19
rpa_control_reciprocal . . . 21
rpa_control_scenario . . . 22
rpacontrol . . . 23
rpanet . . . 23
wdnet_to_igraph . . . 25

Index **27**

`+.rpacontrol` *Add components to the control list*

Description

'+' is used to combine components to control the PA network generation process. Available components are `rpa_control_scenario()`, `rpa_control_edgeweight()`, `rpa_control_newedge()`, `rpa_control_preference()` and `rpa_control_reciprocal()`.

Usage

```
## S3 method for class 'rpacontrol'
e1 + e2
```

Arguments

`e1`	A list of class `rpacontrol`.
`e2`	A list of class `rpacontrol`.

Value

A list of class `rpacontrol` with components from `e1` and `e2`.

Examples

```
control <- rpa_control_scenario(alpha = 0.5, beta = 0.5) +
  rpa_control_preference(
    ftype = "customized",
    spref = "pow(outs, 2) + 1",
    tpref = "pow(ins, 2) + 1"
  )


control <- rpa_control_scenario(alpha = 1) +
  rpa_control_edgeweight(
    sampler = function(n) rgamma(n, shape = 5, scale = 0.2)
  )
```

---

adj_to_wdnet *Creates a* wdnet *object using an adjacency matrix*

Description

Creates a wdnet object using an adjacency matrix

Usage

```
adj_to_wdnet(adj, directed = TRUE, weighted = TRUE, nodegroup, ...)
```

Arguments

adj	An adjacency matrix used to extract edgelist and edgeweight using igraph.
directed	Logical, whether the network is directed (TRUE) or undirected (FALSE). If adj is asymmetric, the network is directed.
weighted	Logical, whether the network is weighted (TRUE) or unweighted (FALSE).
nodegroup	A numeric vector of node groups.
...	Additional components to be added to the wdnet object.

Value

A wdnet object with the specified adj.

Examples

```
adj <- matrix(c(0, 1, 2, 0), nrow = 2, ncol = 2, byrow = TRUE)
adj_to_wdnet(adj = adj, directed = TRUE, weighted = FALSE)
```

assortcoef *Compute the assortativity coefficient(s) for a network.*

Description

Compute the assortativity coefficient(s) for a network.

Usage

```
assortcoef(netwk, edgelist, edgeweight, adj, directed, f1, f2)
```

Arguments

netwk	A wdnet object that represents the network. If NULL, the function will compute the coefficient using either edgelist and edgeweight, or adj.
edgelist	A two-column matrix representing edges.
edgeweight	A numeric vector of edge weights with the same length as the number of rows in edgelist. If NULL, all edges will be assigned weight 1.
adj	The adjacency matrix of a network.
directed	Logical. Indicates whether the edges in edgelist or adj are directed. It will be omitted if netwk is provided.
f1	A vector representing the first feature of existing nodes. The number of nodes should be equal to the length of both f1 and f2. Defined for directed networks. If NULL, out-strength will be used.
f2	A vector representing the second feature of existing nodes. Defined for directed networks. If NULL, in-strength will be used.

Value

Assortativity coefficient for undirected networks, or a list of four assortativity coefficients for directed networks.

Note

When the adjacency matrix is binary (i.e., directed but unweighted networks), assortcoef returns the assortativity coefficient proposed in Foster et al. (2010).

References

- Foster, J.G., Foster, D.V., Grassberger, P. and Paczuski, M. (2010). Edge direction and the structure of networks. *Proceedings of the National Academy of Sciences of the United States*, 107(24), 10815–10820.
- Yuan, Y. Zhang, P. and Yan, J. (2021). Assortativity coefficients for weighted and directed networks. *Journal of Complex Networks*, 9(2), cnab017.

Examples

```
set.seed(123)
control <- rpa_control_edgeweight(
  sampler = function(n) rgamma(n, shape = 5, scale = 0.2)
)
netwk <- rpanet(nstep = 10^4, control = control)
assortcoef(netwk)
assortcoef(
  edgelist = netwk$edgelist,
  edgeweight = netwk$edge.attr$weight,
  directed = TRUE
)
```

---

centrality *Centrality measures*

Description

Computes the centrality measures of the nodes in a weighted and directed network.

Usage

```
centrality(
  netwk,
  adj,
  edgelist,
  edgeweight,
  directed = TRUE,
  measure = c("degree", "closeness", "wpr"),
  degree.control = list(alpha = 1, mode = "out"),
 closeness.control = list(alpha = 1, mode = "out", method = "harmonic", distance =
    FALSE),
  wpr.control = list(gamma = 0.85, theta = 1, prior.info = NULL)
)
```

Arguments

netwk	A wdnet object that represents the network. If NULL, the function will compute the coefficient using either edgelist and edgeweight, or adj.
adj	An adjacency matrix of a weighted and directed network.
edgelist	A two-column matrix representing edges of a directed network.
edgeweight	A vector representing the weight of edges.
directed	Logical. Indicates whether the edges in edgelist or adj are directed.
measure	Which measure to use: "degree" (degree-based centrality), "closeness" (closeness centrality), or "wpr" (weighted PageRank centrality)?

`degree.control` A list of parameters passed to the degree centrality measure:

- ‘alpha‘ A tuning parameter. The value of alpha must be nonnegative. By convention, alpha takes a value from 0 to 1 (default).
- ‘mode‘ Which mode to compute: "out" (default) or "in"? For undirected networks, this setting is irrelevant.

`closeness.control`

A list of parameters passed to the closeness centrality measure:

- ‘alpha‘ A tuning parameter. The value of alpha must be nonnegative. By convention, alpha takes a value from 0 to 1 (default).
- ‘mode‘ Which mode to compute: "out" (default) or "in"? For undirected networks, this setting is irrelevant.
- ‘method‘ Which method to use: "harmonic" (default) or "standard"?
- ‘distance‘ Whether to consider the entries in the adjacency matrix as distances or strong connections. The default setting is `FALSE`.

`wpr.control` A list of parameters passed to the weighted PageRank centrality measure:

- ‘gamma‘ The damping factor; it takes 0.85 (default) if not given.
- ‘theta‘ A tuning parameter leveraging node degree and strength; theta = 0 does not consider edge weight; theta = 1 (default) fully considers edge weight.
- ‘prior.info‘ Vertex-specific prior information for restarting when arriving at a sink. When it is not given (`NULL`), a random restart is implemented.

Value

A list of node names and associated centrality measures

Note

The degree-based centrality measure is an extension of function `strength` in package `igraph` and an alternative of function `degree_w` in package `tnet`.

The closeness centrality measure is an extension of function `closeness` in package `igraph` and function `closeness_w` in package `tnet`. The method of computing distances between vertices is the *Dijkstra's algorithm*.

The weighted PageRank centrality measure is an extension of function `page_rank` in package `igraph`.

References

- Dijkstra, E.W. (1959). A note on two problems in connexion with graphs. *Numerische Mathematik*, 1, 269–271.
- Newman, M.E.J. (2003). The structure and function of complex networks. *SIAM review*, 45(2), 167–256.
- Opsahl, T., Agneessens, F., Skvoretz, J. (2010). Node centrality in weighted networks: Generalizing degree and shortest paths. *Social Networks*, 32, 245–251.

- Zhang, P., Wang, T. and Yan, J. (2022) PageRank centrality and algorithms for weighted, directed networks with applications to World Input-Output Tables. *Physica A: Statistical Mechanics and its Applications*, 586, 126438.
- Zhang, P., Zhao, J. and Yan, J. (2020+) Centrality measures of networks with application to world input-output tables

Examples

```
## Generate a network according to the Erd\"{o}s-Renyi model of order 20
## and parameter p = 0.3
edge_ER <- rbinom(400, 1, 0.3)
weight_ER <- sapply(edge_ER, function(x) x * sample(3, 1))
adj_ER <- matrix(weight_ER, 20, 20)
mydegree <- centrality(
  adj = adj_ER,
  measure = "degree", degree.control =
    list(alpha = 0.8, mode = "in")
)
myclose <- centrality(
  adj = adj_ER,
  measure = "closeness", closeness.control =
    list(alpha = 0.8, mode = "out", method = "harmonic", distance = FALSE)
)
mywpr <- centrality(
  adj = adj_ER,
  measure = "wpr", wpr.control =
    list(gamma = 0.85, theta = 0.75)
)
```

---

clustcoef *Directed clustering coefficient*

Description

Compute the clustering coefficient of a weighted and directed network.

Usage

```
clustcoef(
  netwk,
  edgelist,
  edgeweight,
  adj,
  directed = TRUE,
  method = c("Clemente", "Fagiolo"),
  isolates = 0
)
```

Arguments

netwk	A wdnet object that represents the network. If NULL, the function will compute the coefficient using either edgelist, edgeweight, or adj.
edgelist	A two-column matrix, each row represents a directed edge of the network.
edgeweight	A vector representing the weight of edges.
adj	An adjacency matrix of a weighted and directed network.
directed	Logical. Indicates whether the edges in edgelist or adj are directed.
method	Which method used to compute clustering coefficients: Clemente and Grassi (2018) or Fagiolo (2007).
isolates	Binary, defines how to treat vertices with degree zero and one. If 0, then their clustering coefficient is returned as 0 and are included in the averaging. Otherwise, their clustering coefficient is NaN and are excluded in the averaging. Default value is 0.

Value

Lists of local clustering coefficients (in terms of a vector), global clustering coefficient (in terms of a scalar) and number of weighted directed triangles (in terms of a vector) based on total, in, out, middleman (middle), or cycle triplets.

Note

Self-loops (if exist) are removed prior to the computation of clustering coefficient. When the adjacency matrix is symmetric (i.e., undirected but possibly unweighted networks), clustcoef returns local and global clustering coefficients proposed by Barrat et al. (2010).

References

- Barrat, A., Barthelemy, M., Pastor-Satorras, R. and Vespignani, A. (2004). The architecture of complex weighted networks. *Proceedings of National Academy of Sciences of the United States of America*, 101(11), 3747–3752.
- Clemente, G.P. and Grassi, R. (2018). Directed clustering in weighted networks: A new perspective. *Chaos, Solitons & Fractals*, 107, 26–38.
- Fagiolo, G. (2007). Clustering in complex directed networks. *Physical Review E*, 76, 026107.

Examples

```
## Generate a network according to the Erd\"{o}s-Renyi model of order 20
## and parameter p = 0.3
edge_ER <- rbinom(400, 1, 0.3)
weight_ER <- sapply(edge_ER, function(x) x * sample(3, 1))
adj_ER <- matrix(weight_ER, 20, 20)
mycc <- clustcoef(adj = adj_ER, method = "Clemente")
system.time(mycc)
```

cvxr_control *Parameters passed to CVXR::psolve().*

Description

Defined for the convex optimization problems for solving `eta`.

Usage

```
cvxr_control(
  solver = "CLARABEL",
  warm_start = FALSE,
  verbose = FALSE,
  gp = FALSE,
  feastol = 1e-05,
  reltol = 1e-05,
  abstol = 1e-05,
  num_iter = NULL,
  ...
)
```

Arguments

`solver`	(Optional) A string indicating the solver to use. Defaults to "CLARABEL". the DCP check for a problem.
`warm_start`	(Optional) A logical value indicating whether the previous solver result should be used to warm start.
`verbose`	(Optional) A logical value indicating whether to print additional solver output.
`gp`	(Optional) A logical value indicating whether the problem is a geometric program. Defaults to FALSE.
`feastol`	The feasible tolerance on the primal and dual residual. Defaults to 1e-5.
`reltol`	The relative tolerance on the duality gap. Defaults to 1e-5.
`abstol`	The absolute tolerance on the duality gap. Defaults to 1e-5.
`num_iter`	The maximum number of iterations.
`...`	Additional options that will be passed to the specific solver. In general, these options will override any default settings imposed by CVXR.

Value

A list containing the parameters.

Examples

```
control <- cvxr_control(solver = "OSQP", abstol = 1e-5)
```

dprewire *Degree preserving rewiring.*

Description

Rewire a given network to have predetermined assortativity coefficient(s) while preserving node degree.

Usage

```
dprewire(
  netwk,
  edgelist,
  directed,
  adj,
  target.assortcoef = list(outout = NULL, outin = NULL, inout = NULL, inin = NULL),
  control = list(iteration = 200, nattempts = NULL, history = FALSE, cvxr_control =
    cvxr_control(), eta.obj = function(x) 0),
  eta
)
```

Arguments

netwk	A wdnet object representing an unweighted network. If NULL, the function will construct a network using either edgelist, or adj.
edgelist	A two column matrix, each row represents an edge of the network.
directed	Logical, whether the network is directed or not. It will be ignored if netwk is provided.
adj	An adjacency matrix of an unweighted network.
target.assortcoef	For directed networks, it is a list represents the predetermined value or range of assortativity coefficients. For undirected networks, it is a constant between -1 to 1. It will be ignored if eta is provided.
control	A list of parameters for controlling the rewiring process and the process for solving eta.

- 'iteration' An integer, represents the number of rewiring iterations. Each iteration consists of nattempts rewiring attempts. The assortativity coefficient(s) of the network will be recorded after each iteration.
- 'nattempts' An integer representing the number of rewiring attempts for each iteration. Default value equals the number of rows of edgelist.
- 'history' Logical, whether the rewiring attempts should be recorded and returned.
- 'eta.obj' A convex function of eta to be minimized when solving for eta with given target.assortcoef. Defaults to 0. It will be ignored if eta is provided.

- ‘cvxr_control‘ A list of parameters passed to `CVXR::psolve()` for solving `eta` with given `target.assortcoef`. It will be ignored if `eta` is provided.

`eta` A matrix represents the target network structure. If specified, `target.assortcoef` will be ignored. For directed networks, the element at row "i-j" and column "k-l" represents the proportion of directed edges linking a source node with out-degree i and in-degree j to a target node with out-degree k and in-degree l. For undirected networks, `eta` is symmetric, the summation of the elements at row "i", column "j" and row "j", column "i" represents the proportion of edges linking to a node with degree i and a node with degree j.

Details

The algorithm first solves for an appropriate `eta` using `target.assortcoef`, `eta.obj`, and `cvxr_control`, then proceeds to the rewiring process and rewire the network towards the solved `eta`. If `eta` is given, the algorithm will skip the first step. This function only works for unweighted networks.

Each rewiring attempt samples two rows from `edgelist`, for instance Edge 1:(v_1, v_2) and Edge 2:(v_3, v_4). For directed networks, if the rewiring attempt is accepted, the sampled edges are rewired as (v_1, v_4), (v_3, v_2); for undirected networks, the algorithm try to rewire the sampled edges as {v_1, v_4}, {v_3, v_2} (type 1) or {v_1, v_3}, {v_2, v_4} (type 2), each with probability 1/2.

Value

Rewired network; assortativity coefficient(s) after each iteration; rewiring history (including the index of sampled edges and rewiring result) and solver results.

Examples

```
set.seed(123)
netwk1 <- rpanet(1e4, control = rpa_control_scenario(
  alpha = 0.4, beta = 0.3, gamma = 0.3
))
## rewire a directed network
target.assortcoef <- list("outout" = -0.2, "outin" = 0.2)
ret1 <- dprewire(
  netwk = netwk1,
  target.assortcoef = target.assortcoef,
  control = list(iteration = 200)
)
plot(ret1$assortcoef$Iteration, ret1$assortcoef$"outout")
plot(ret1$assortcoef$Iteration, ret1$assortcoef$"outin")

## rewire an undirected network
set.seed(123)
netwk2 <- rpanet(1e4,
  control = rpa_control_scenario(
    alpha = 0.3, beta = 0.1, gamma = 0.3, xi = 0.3
  ),
  initial.network = list(
    directed = FALSE)
```

```
)
ret2 <- dprewire(
  netwk = netwk2,
  target.assortcoef = 0.3,
  control = list(
    iteration = 500, eta.obj = CVXR::norm2,
    history = TRUE
  )
)
plot(ret2$assortcoef$Iteration, ret2$assortcoef$Value)
```

`dprewire.range` *Range of assortativity coefficients.*

Description

The assortativity coefficient of a given network may not reach all the values between -1 and 1 via degree preserving rewiring. This function calculates the range of assortativity coefficients achievable through degree preserving rewiring. The algorithm is designed for unweighted networks.

Usage

```
dprewire.range(
  netwk,
  edgelist,
  adj,
  directed,
  which.range = c("outout", "outin", "inout", "inin"),
  control = cvxr_control(),
  target.assortcoef = list(outout = NULL, outin = NULL, inout = NULL, inin = NULL)
)
```

Arguments

`netwk`	A `wdnet` object representing an unweighted network. If `NULL`, the function will construct a network using either `edgelist` or `adj`.
`edgelist`	A two-column matrix, where each row represents an edge of the network.
`adj`	An adjacency matrix of an unweighted network.
`directed`	Logical, whether the network is directed or not. It will be ignored if `netwk` is provided.
`which.range`	The type of interested assortativity coefficient. For directed networks, it takes one of the values: "outout", "outin", "inout" and "inin". It will be ignored if the network is undirected.
`control`	A list of parameters passed to `CVXR::psolve()` for solving an appropriate `eta`, given the constraints `target.assortcoef`.

target.assortcoef
: A list of constraints, it contains the predetermined value or range imposed on assortativity coefficients other than which.range. It will be ignored if the network is undirected.

Details

The ranges are computed using convex optimization. The optimization problems are defined and solved via the R package CVXR. For undirected networks, the function returns the range of the assortativity coefficient. For directed networks, the function computes the range of which.range while other assortativity coefficients are restricted through target.assortcoef.

Value

Returns the range of the selected assortativity coefficient and the results from the solver.

Examples

```
set.seed(123)
netwk <- rpanet(5e3,
  control =
    rpa_control_scenario(alpha = 0.5, beta = 0.5)
)
ret1 <- dprewire.range(
  netwk = netwk, which.range = "outin",
  target.assortcoef = list("outout" = c(-0.3, 0.3), "inout" = 0.1)
)
ret1$range
```

---

edgelist_to_wdnet *Creates a* wdnet *object using* edgelist.

Description

Creates a wdnet object using edgelist.

Usage

```
edgelist_to_wdnet(edgelist, edgeweight, directed, nodegroup, ...)
```

Arguments

edgelist	A two-column matrix representing the edges.
edgeweight	A numeric vector of edge weights with the same length as the number of rows in edgelist. If NULL, all edges will be assigned weight 1.
directed	Logical, whether the network is directed (TRUE) or undirected (FALSE).
nodegroup	A numeric vector of node groups.
...	Additional components to be added to the wdnet object.

Value

A wdnet object with the specified edgelist, edgeweight and directed.

Examples

```
edgelist <- matrix(c(1, 2, 2, 3, 3, 1), ncol = 2, byrow = TRUE)
edgeweight <- c(1, 2, 3)
nodegroup <- c(1, 1, 2)
netwk <- edgelist_to_wdnet(
  edgelist = edgelist,
  edgeweight = edgeweight,
  directed = TRUE,
  nodegroup = nodegroup
)
```

---

igraph_to_wdnet *Converts an* igraph *object to a* wdnet *object*

Description

Converts an igraph object to a wdnet object

Usage

```
igraph_to_wdnet(g)
```

Arguments

g	An igraph object.

Value

A wdnet object.

Examples

```
g <- igraph::sample_pa(50)
netwk <- igraph_to_wdnet(g)
```

is_wdnet *Checks if the input is a* wdnet *object*

Description

Checks if the input is a wdnet object

Usage

```
is_wdnet(netwk)
```

Arguments

netwk	A wdnet object.

Value

Logical, TRUE if argument netwk is a wdnet object.

Examples

```
netwk <- rpanet(nstep = 1e3)
is_wdnet(netwk)
```

plot.wdnet *Plots the input network*

Description

Plots the input network via igraph::plot.igraph().

Usage

```
## S3 method for class 'wdnet'
plot(x, ...)
```

Arguments

x	A wdnet object.
...	Additional parameters passed to igraph::plot.igraph().

Value

Returns NULL, invisibly.

print.rpacontrol *Prints* rpacontrol *objects*

Description

These functions print rpacontrol objects in the terminal. print.rpacontrol() shows only the current controls, whereas summary.rpacontrol() includes both specified controls and the unspecified controls that use default values.

Usage

```
## S3 method for class 'rpacontrol'
print(x, ...)

## S3 method for class 'rpacontrol'
summary(object, ...)
```

Arguments

x	An object of class rpacontrol.
...	Additional arguments.
object	An object of class rpacontrol.

Value

Returns the controls invisibly.

Examples

```
control <- rpa_control_scenario()
print(control)
```

print.wdnet *Prints the input network*

Description

These functions print a network to the terminal.

Usage

```
## S3 method for class 'wdnet'
print(x, node.attrs = TRUE, edge.attrs = TRUE, max.lines = 5, ...)

## S3 method for class 'wdnet'
summary(object, ...)
```

Arguments

x	A wdnet object.
node.attrs	Logical, whether to print node attributes, if available.
edge.attrs	Logical, whether to print edge attributes, if available.
max.lines	Integer, the maximum number of lines of edgelist and node attributes to print. The rest of the output will be truncated.
...	Additional arguments.
object	The graph of which the summary will be printed.

Details

summary.wdnet prints the number of nodes and edges, preference functions, and whether the network is directed, weighted. print.wdnet prints the same information, and also lists some edges and node attributes, if available. Edge scenarios are 0: from initial network; 1: alpha; 2: beta; 3: gamma; 4: xi; 5; rho; 6: reciprocal.

---

rpa_control_edgeweight

Control weight of new edges. Defined for rpanet.

Description

Control weight of new edges. Defined for rpanet.

Usage

```
rpa_control_edgeweight(sampler = NULL)
```

Arguments

sampler	A function used for sampling edge weights. If NULL, all new edges will default to a weight of 1. If a function is provided, it must accept a single argument, n, and return a vector of length n that represents the sampled edge weights.

Value

A list of class rpacontrol containing the sampler function.

Examples

```
# Sample edge weights from Gamma(5, 0.2).
my_gamma <- function(n) rgamma(n, shape = 5, scale = 0.2)
control <- rpa_control_edgeweight(
  sampler = my_gamma
)
```

rpa_control_newedge *Control new edges in each step. Defined for* rpanet.

Description

Control new edges in each step. Defined for rpanet.

Usage

```
rpa_control_newedge(
  sampler = NULL,
  snode.replace = TRUE,
  tnode.replace = TRUE,
  node.replace = TRUE
)
```

Arguments

sampler	A function used for sampling the number of new edges to be added at each step. If NULL, one new edge will be added at each step. If a function is provided, it must accept a single argument, n, and return a vector of length n that represents the sampled number of new edges.
snode.replace	Logical. Determines whether the source nodes in the same step should be sampled with replacement. Defined for directed networks.
tnode.replace	Logical. Determines whether the target nodes in the same step should be sampled with replacement. Defined for directed networks.
node.replace	Logical. Determines whether the nodes in the same step should be sampled with replacement. Defined for undirected networks. If FALSE, self-loops will not be allowed under beta scenario.

Value

A list of class rpacontrol with components sampler, snode.replace, tnode.replace and node.replace with meanings as explained under 'Arguments'.

Examples

```
my_rpois <- function(n) rpois(n, lambda = 2) + 1
control <- rpa_control_newedge(
  sampler = my_rpois,
  node.replace = FALSE
)
```

rpa_control_preference *Set preference function(s). Defined for* rpanet.

Description

Set preference function(s). Defined for rpanet.

Usage

```
rpa_control_preference(
  ftype = c("default", "customized"),
  sparams = c(1, 1, 0, 0, 1),
  tparams = c(0, 0, 1, 1, 1),
  params = c(1, 1),
  spref = "outs + 1",
  tpref = "ins + 1",
  pref = "s + 1"
)
```

Arguments

ftype	Preference function type. Either "default" or "customized". "customized" preference functions require "binary" or "linear" generation methods. If using default preference functions, sparams, tparams and params must be specified. If using customized preference functions, spref, tpref and pref must be specified.
sparams	A numerical vector of length 5 giving the parameters of the default source preference function. Defined for directed networks. Probability of choosing an existing node as the source node is proportional to sparams[1] * out-strength^sparams[2] + sparams[3] * in-strength^sparams[4] + sparams[5].
tparams	A numerical vector of length 5 giving the parameters of the default target preference function. Defined for directed networks. Probability of choosing an existing node as the target node is proportional to tparams[1] * out-strength^tparams[2] + tparams[3] * in-strength^tparams[4] + tparams[5].
params	A numerical vector of length 2 giving the parameters of the default preference function. Defined for undirected networks. Probability of choosing an existing node is proportional to strength^params[1] + params[2].
spref	Character expression or an object of class XPtr giving the customized source preference function. Defined for directed networks. Default value is "outs + 1", i.e., node out-strength + 1. See Details and Examples for more information.
tpref	Character expression or an object of class XPtr giving the customized target preference function. Defined for directed networks. Default value is "ins + 1", i.e., node in-strength + 1.

`pref` Character expression or an object of class `XPtr` giving the customized preference function. Defined for undirected networks. Default value is `"s + 1"`, i.e, node strength + 1.

Details

If choosing customized preference functions, `spref`, `tpref` and `pref` will be used and the network generation method must be "binary" or "linear". `spref` (`tpref`) defines the source (target) preference function, it can be a character expression or an object of class `XPtr`.

- Character expression; it must be a one-line `C++` style expression of `outs` (node out-strength) and `ins` (node in-strength). For example, `"pow(outs, 2) + 1"`, `"pow(outs, 2) + pow(ins, 2) + 1"`, etc. The expression will be used to define an `XPtr` via `RcppXPtrUtils::cppXPtr`. The `XPtr` will be passed to the network generation function. The expression must not have variables other than `outs` and `ins`.
- 'XPtr' an external pointer wrapped in an object of class `XPtr` defined via `RcppXPtrUtils::cppXPtr`. An example for defining an `XPtr` with `C++` source code is included in Examples. For more information about passing function pointers, see https://gallery.rcpp.org/articles/passing-cpp-function-pointers-rcppxptrutils/. Please note the supplied `C++` function accepts two `double` arguments and returns a `double`. The first and second arguments represent node out- and in-strength, respectively. Note that the `XPtr` will be invalid and cannot be used to control network generation in another separate R session. Therefore, we recommend preserving the source code of your preference function for future use.

`pref` is defined analogously. If using character expression, it must be a one-line `C++` style expression of `s` (node strength). If using `XPtr`, the supplied `C++` function accepts only one `double` argument and returns a `double`.

Value

A list of class `rpacontrol` with components `ftype`, `sparams`, `tparams`, `params` or `ftype`, `spref`, `tpref`, `pref` with function pointers `spref.pointer`, `tpref.pointer`, `pref.pointer`.

Examples

```
# Set source preference as out-strength^2 + in-strength + 1,
# target preference as out-strength + in-strength^2 + 1.
# 1. use default preference functions
ctr1 <- rpa_control_preference(
  ftype = "default",
  sparams = c(1, 2, 1, 1, 1), tparams = c(1, 1, 1, 2, 1)
)
# 2. use character expressions
ctr2 <- rpa_control_preference(
  ftype = "customized",
  spref = "pow(outs, 2) + ins + 1", tpref = "outs + pow(ins, 2) + 1"
)
# 3. define XPtr's with C++ source code
spref.pointer <- RcppXPtrUtils::cppXPtr(
  code =
    "double spref(double outs, double ins) {return pow(outs, 2) + ins + 1;}"
```

```
)
tpref.pointer <- RcppXPtrUtils::cppXPtr(
  code =
    "double tpref(double outs, double ins) {return outs + pow(ins, 2) + 1;}"
)
ctr3 <- rpa_control_preference(
  ftype = "customized",
  spref = spref.pointer,
  tpref = tpref.pointer
)
ret <- rpanet(1e5, control = ctr3)
```

`rpa_control_reciprocal` *Control reciprocal edges. Defined for* `rpanet`.

Description

Control reciprocal edges. Defined for `rpanet`.

Usage

```
rpa_control_reciprocal(
  group.prob = NULL,
  recip.prob = NULL,
  selfloop.recip = FALSE
)
```

Arguments

`group.prob`	A vector of probability weights for sampling the group of new nodes. Defined for directed networks. Groups are from 1 to `length(group.prob)`. Its length must equal to the number of rows of `recip.prob`.
`recip.prob`	A square matrix giving the probability of adding a reciprocal edge after a new edge is introduced. Defined for directed networks. Its element `p_{ij}` represents the probability of adding a reciprocal edge from node `A`, which belongs to group `i`, to node `B`, which belongs to group `j`, immediately after a directed edge from `B` to `A` is added.
`selfloop.recip`	Logical, whether reciprocal edge of self-loops are allowed.

Value

A list of class `rpacontrol` with components `group.prob`, `recip.prob`, and `selfloop.recip` with meanings as explained under 'Arguments'.

Examples

```
control <- rpa_control_reciprocal(
  group.prob = c(0.4, 0.6),
  recip.prob = matrix(runif(4), ncol = 2)
)
```

`rpa_control_scenario` *Control edge scenarios. Defined for* `rpanet`.

Description

Control edge scenarios. Defined for `rpanet`.

Usage

```
rpa_control_scenario(
  alpha = 1,
  beta = 0,
  gamma = 0,
  xi = 0,
  rho = 0,
  beta.loop = TRUE,
  source.first = TRUE
)
```

Arguments

`alpha`	Probability of adding an edge from a new node to an existing node.
`beta`	Probability of adding an edge between existing nodes.
`gamma`	Probability of adding an edge from an existing node to a new node.
`xi`	Probability of adding an edge between two new nodes.
`rho`	Probability of adding a new node with a self-loop.
`beta.loop`	Logical. Determines whether self-loops are allowed under the beta scenario. Default value is `TRUE`.
`source.first`	Logical. Defined for `beta` scenario edges of directed networks. If `TRUE`, the source node of a new edge is sampled from existing nodes before the target node is sampled; if `FALSE`, the target node is sampled from existing nodes before the source node is sampled. Default value is `TRUE`.

Value

A list of class `rpacontrol` with components `alpha`, `beta`, `gamma`, `xi`, `rho`, `beta.loop` and `source.first` with meanings as explained under 'Arguments'.

Examples

```
control <- rpa_control_scenario(alpha = 0.5, beta = 0.5, beta.loop = FALSE)
```

rpacontrol *rpacontrol: Controls the Preferential Attachment (PA) Network Generation Process*

Description

The `rpacontrol` object is designed to control the Preferential Attachment (PA) network generation process within the `rpanet()` function. It can have the following components:

- `scenario`: controls the edge scenarios at each step. For more information, please refer to `rpa_control_scenario()`.
- `edgeweight`: controls the weight of the edges; see `rpa_control_edgeweight()` for details.
- `newedge`: controls the creation of new edges at each step; see `rpa_control_newedge()` for details.
- `preference`: sets preference functions; see `rpa_control_preference()` for details.
- `reciprocal`: controls the creation of reciprocal edges; see `rpa_control_reciprocal()` for details.

rpanet *Generate PA networks.*

Description

Generate preferential attachment (PA) networks with linear or non-linear preference functions.

Usage

```
rpanet(
  nstep,
  initial.network = list(edgelist = matrix(c(1, 2), nrow = 1), edgeweight = 1, directed =
    TRUE),
  control,
  method = c("binary", "linear", "bagx", "bag")
)
```

Arguments

`nstep`	Number of steps.
`initial.network`	A `wdnet` object or a list representing the initial network. By default, `initial.network` has one directed edge from node 1 to node 2 with weight 1. It can contain the following components: a two-column matrix `edgelist` representing the edges; a vector `edgeweight` representing the weight of edges; a logical argument `directed` indicating whether the initial network is directed. If `edgeweight`

is not specified, all edges from the initial network are assumed to have weight 1. In addition, an integer vector `nodegroup` can be added to the list for specifing node groups; `nodegroup` is defined for directed networks, if `NULL`, all nodes from the seed network are assumed to be in group 1.

`control` An `rpacontrol` object controlling the PA network generation process. If not specified, all the control parameters will be set to default. For more details, see `rpa_control_scenario()`, `rpa_control_newedge()`, `rpa_control_edgeweight()`, `rpa_control_preference` and `rpa_control_reciprocal()`. Under the default setup, at each step, a new edge of weight 1 is added from a new node `A` to an existing node `B` (`alpha` scenario), where `B` is chosen with probability proportional to its in-strength + 1.

`method` Which method to use: `binary`, `linear`, `bagx` or `bag`. For `bag` and `bagx` methods, `beta.loop` must be `TRUE`, default preference functions must be used, and `sparams` should be set to `c(1, 1, 0, 0, a)`, `tparams` to `c(0, 0, 1, 1, b)`, and `param` to `c(1, c)`, where `a`, `b`, and `c` are non-negative constants; furthermore, reciprocal edges and sampling without replacement are not considered, i.e., option `rpa_control_reciprocal()` must be set as default, `snode.replace`, `tnode.replace` and `node.replace` must be `TRUE`. In addition, `bag` method only works for unweighted networks and does not consider multiple edges, i.e., `rpa_control_edgeweight()` and `rpa_control_newedge()` must be set as default.

Value

Returns a `wdnet` object that includes the following components:

- `directed`: Logical, whether the network is directed.
- `weighted`: Logical, whether the network is weighted.
- `edgelist`: A two-column matrix representing the edges.
- `edge.attr`: A data frame including edge weights and edge scenarios (0: from initial network; 1: `alpha`; 2: `beta`; 3: `gamma`; 4: `xi`; 5; `rho`; 6: reciprocal edge).
- `node.attr`: A data frame including node out- and in-strength, node source and target preference scores (for directed networks), node strength and preference scores (for undirected networks), and node group (if applicable).
- `newedge`: The number of new edges at each step, including reciprocal edges.
- `control`: An `rpacontrol` object that is used to generate the network.

Note

The `binary` method implements binary search algorithm; `linear` represents linear search algorithm; `bag` method implements the algorithm from Wan et al. (2017); `bagx` puts all the edges into a bag, then samples edges and find the source/target node of the sampled edge.

References

- Wan P, Wang T, Davis RA, Resnick SI (2017). Fitting the Linear Preferential Attachment Model. Electronic Journal of Statistics, 11(2), 3738–3780.

Examples

```
# Control edge scenario and edge weight through rpa_control_scenario()
# and rpa_control_edgeweight(), respectively,
# while keeping rpa_control_newedge(),
# rpa_control_preference() and rpa_control_reciprocal() as default.
set.seed(123)
control <- rpa_control_scenario(alpha = 0.5, beta = 0.5) +
  rpa_control_edgeweight(
    sampler = function(n) rgamma(n, shape = 5, scale = 0.2)
  )
ret1 <- rpanet(nstep = 1e3, control = control)

# In addition, set node groups and probability of creating reciprocal edges.
control <- control + rpa_control_reciprocal(
  group.prob = c(0.4, 0.6),
  recip.prob = matrix(runif(4), ncol = 2)
)
ret2 <- rpanet(nstep = 1e3, control = control)

# Further, set the number of new edges in each step as Poisson(2) + 1 and use
# ret2 as a seed network.
control <- control + rpa_control_newedge(
  sampler = function(n) rpois(n, lambda = 2) + 1
)
ret3 <- rpanet(nstep = 1e3, initial.network = ret2, control = control)
```

---

wdnet_to_igraph *Converts a* wdnet *object to an* igraph *object*

Description

Converts a wdnet object to an igraph object

Usage

```
wdnet_to_igraph(netwk)
```

Arguments

netwk	A wdnet object.

Value

An igraph object.

Examples

```
netwk <- rpanet(nstep = 1e3)
g <- wdnet_to_igraph(netwk)
```

Index

+.rpacontrol, 2

adj_to_wdnet, 3
assortcoef, 4

centrality, 5
clustcoef, 7
cvxr_control, 9

dprewire, 10
dprewire.range, 12

edgelist_to_wdnet, 13

igraph_to_wdnet, 14
is_wdnet, 15

plot.wdnet, 15
print.rpacontrol, 16
print.wdnet, 16

rpa_control_edgeweight, 17
rpa_control_newedge, 18
rpa_control_preference, 19
rpa_control_reciprocal, 21
rpa_control_scenario, 22
rpacontrol, 23
rpanet, 23

summary.rpacontrol *(*print.rpacontrol*)*, 16
summary.wdnet *(*print.wdnet*)*, 16

wdnet_to_igraph, 25